

PRIMARY CORNER DESCRIPTION Sec. Cor. for 23, 24, 25 and 26

Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - W.H. Byars, under contract # 376 dated Jan. 22, 1881 (DCSO rec. Vol. 13 Pages 5616)

-----  
 Set Cedar post for cor. to secs. 23, 24, 25, 26, from which  
 Laurel 10" dia., bears N.60°E., 37 lks.  
 Fir 8" dia., bears S.20°E., 25 lks.  
 Laurel 20" dia., bears S.25°W., 45 lks.  
 Fir 24" dia., bears N.8°W., 50 lks.

BLM resurvey by Zirpel and Glenn under Special Instructions dated August 29, 1957 (DCSO records, Vol. 29 page 12225)

-----  
 Point for the sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd:

|          |      |
|----------|------|
| T28S R4W |      |
| S 23     | S 24 |
| S 26     | S 25 |
| 1958     |      |

from which

- A Pine 5" dia., bears N.55¼°E., 27 lks. dist. marked  
T28S R4W S24 BT.
- A Madrone 8" dia., bears S.56½°E., 63 lks. dist. marked  
T28S R4W S25 BT.
- A Pine 6" dia., bears S.50¼°W., 60 lks. dist. marked  
T28S R4W S26 BT.
- A Fir 36" dia., bears N.45°W., 42 lks. dist., marked  
T28S R4W S23 BT.

Ron Rice, Ward NW Inc. - For: Seneca Jones Timber Co. - Nov. 2002 - M 147-27

-----  
 Found - 3" BLM BC dated 1958 with the following accessories:  
 19" Pine bears N.55¼°E., 17.8 ft. with healed face.  
 14" Madrone snag bears S.56½°E., 41.6 ft. with scribing visible.  
 Record Pine S.50¼°W., missing.  
 Record Fir N.45°W., down out of position

New BTs this survey

- 17" D.Fir bears S.34°W., 23.2 ft. blazed, scribed  
"T28S R4W S26 BT"
- 16" D.Fir bears N.11°W., 33.4 ft. blazed, scribed  
"T28S R4W S23 BT"
- 10" D.Fir bears S.3°E., 46.2 ft. blazed, scribed  
"T28S R4W S25 BT"

All accessories have tags, red paint plus steel post adjacent to corner.

cont

TOWNSHIP 28 RANGE 04 POINT IDENTIFIER # 600300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 23, 24, 25 and 26

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Ken Hoffine - For: Lone Rock Timber Co - Jan. 2020 - C.S.  
File 65/105-4

-----  
Found - 1958 BLM brass cap as per BLM dependant resurvey 0.1  
ft. above ground.

19" D.Fir bears N.13¼°W., 33.0 ft (2002 record  
N.11°W., 33.4 ft) healed face & tag.

19" D.Fir bears S.28¾°W., 23.8 ft (2002 record  
S.34°W., 23.2 ft.) healed face and tag.

12" D.Fir bears S.5¾°E., 46.0 ft healed face and tag  
(2002 record S3°E., 46.2 ft.)

24" W.Pine bears N.56¼°E., 17.7 ft (1957 record  
N.55¼°E., 17.8 ft.) healed face and tag.

Note - Searched for 14" madrone snag unable to locate per  
2002 record.

Corner lies on east facing slope in timber.

Steel fence post alongside corner.

BTs are blazed and scribed at the root crown with  
distances measured to a nail at the side center  
of the tree. the blazed faces of the bearing  
trees are painted fluorescent red and a bearing  
tree tag is nailed to the tree.