

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 23 & 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W.H. Byars, under contract # 376 dated Jan. 22, 1881 (DCSO rec. Vol. 13 Page 5617)

Set Ash post for ¼ sec. cor., from which
An Ash 16" dia., bears S.65°W., 23 lks.
Fir 12" dia., bears S.65°E., 22 lks. dist.

John H. Markham, For: Mr. Stonerod - June 18, 1953 - C.S. File 41/179

Set from field notes
At corner point: Set 1" x 30" I.P. from which
24" Fir bears S.65°E., 14.5 ft. mkd. ¼ S24 BT.
10" Cedar bears S.47°W/. 50.0 ft. mkd. ¼ S BT.
Corner lies on South edge of North Myrtle Creek.
Fence bears West from corner.

BLM resurvey by Zirpel and Glenn under Special Instructions dated Aug. 29, 1957 (DCSO records, Vol. 29 Pages 12227-28)

The ¼ sec. cor., perpetuated and recorded by Markham, 1953, at record bearing and distance from the original SE BT, monumented with an I.P. 1" dia., firmly set, 8" above ground. from which the original bearing tree

A Fir 33" dia., bears S.65°E., 22 lks. dist., with partially opened blaze, no scribe marks visible.
Rescribed ¼ S24 BT on a bark blaze by Markham bearing tree by Markham

A Cedar 11" dia., bears S.47°W., 77½ lks. dist., with scribe marks ¼ S23 BT visible on partially healed blaze.

At the corner point
Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd: T28S R4W

¼
S23 | S24
1958

from which
A Cedar 12" dia., bears N.75½°E., 45 lks. dist. mkd. ¼ S24 BT.

Reset iron pipe alongside the iron post.

Fd. OK, BLM survey by Jelley, 1965 (DCSO records, Vol. 39 Page 13933)

continued next page

TOWNSHIP 28 RANGE 04 POINT IDENTIFIER # 600340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 23 & 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Ken Hoffine - For: Lone Rock Timber Co - Jan. 2020 - C.S.
File 65/105-4

Found - 1958 BLM brass cap as per BLM dependant resurvey 0.4
ft. above ground
26" Cedar bears S.46 $\frac{3}{4}$ °W 51.2 ft (1957 record S.47°W.
77 $\frac{1}{2}$ lks 51.15 ft.)
29" Cedar bears N.76°E., 28.9 ft (1957 record
N.75 $\frac{1}{2}$ °E., 45 lks 29.70 ft.)
New - 30" Cedar bears S.3 $\frac{3}{4}$ °E., 19 ft we scribe T28S R4W $\frac{1}{4}$
S24 BT and tag tree.
Note - Searched for 33" Fir at S.65°E., 14.52 ft. and was
unable to locate.
Corner lies approx 25' ft from small stream on the
edge of a large vine maple patch .
BTs are blazed and scribed at the root crown with
distances measured to a nail at the side center
of the tree. the blazed faces of the bearing
trees are painted fluorescent red and a bearing
tree tag is nailed to the tree.