

TOWNSHIP 28 RANGE 04 POINT IDENTIFIER # 600400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13, 14, 23 & 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W.H. Byars, under contract # 376 dated Jan. 22, 1881 (DCSO rec. Vol. 13 Pages 5617-18)

Set Laurel post for cor. to secs. 13, 14, 23 & 24, from which
Laurel 14" dia., bears N.32°E., 132 lks.
Laurel 10" dia., bears S.72°E., 106 lks.
Laurel 8" dia., bears S.62°W., 17 lks.
Laurel 7" dia., bears N.60°W., 33 lks.

BLM resurvey by James Jelley, under Group #570 - Survey, June/July 1965 (DCSO records, Vol. 33 Pages 13933-34)

Point for the sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd:

T 28	S R 4 W
S 14	S 13
S 23	S 24
1965	

from which
A Madrone 12" dia., bears N.65°E., 76 lks. dist., mkd. T28S R4W S13 BT.
A Fir 9" dia., bears S.65½°E., 49½ lks. dist., mkd. T28S R4W S24 BT.
A Madrone 28" dia., bears S.78°W., 91 lks. dist., mkd. T28S R4W S23 BT.
A Madrone 10" dia., bears N.29½°W., 32 lks. dist., mkd. T28S R4W S14 BT.

Dan Saily, Lone Rock Timber Co. - Crew: Brett Ragon, Ignacio Roman & Trevor Clemo - 12/2023 - M183-27

Found - 1965 BLM brass cap and iron pipe (properly mkd). The monument is 0.4 ft. above ground on gentle south facing slope, approximately 170' east of large draw running south. We set 5½ ft. galvanized steel post 1 ft north.
15" Pacific Madrone bears N.64°E., 49.8 ft. [N.65°E., 50.16 ft/ 76 lks] has open rotted face and we re-tag
Fir at rec [S.65½°E. 49½ lks] down & out of position
Madrone at rec [S.78°W. 91 lks] down & out of position
New - 8" D.Fir bears S.32¾°E., 31.8 ft. we tag and scribe S24 BT
11" D.Fir bears S.52¾°W., 13.9 ft. we tag and scribe T28S R4W S23 BT
13" D.Fir bears N.63¾°W., 26.4 ft. we tag and scribe T28S R4W S14 BT. _____