

TOWNSHIP 28 RANGE 04 POINT IDENTIFIER # 600440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 13 and 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - W.H. Byars, under contract # 376 dated Jan. 22, 1881 (DCSO rec. Vol. 13 Page 5618)

Set post for 1/4 sec. cor. from which
Fir 20" dia., bears N.35°E., 60 lks.
Hemlock 14" dia., bears N.60°W., 83 lks.

Ben B. Irving, D.C.S. - R.L. Irving; J.R. Stronss; J. Moore
May 16-17, 1927 - C.S. 37/53 and "old" cor. book, Pg. 181

Identified by old Hemlock stump carrying scribe marks and a
36" Fir which bears proper scars which I did not chop out.
Set post for corner and marked a
Hemlock 10" dia., bears S.54°10'W., 11.9 ft.
I remarked OBT
Leaning Fir, 36" dia., bears N.35°E., 36.6 ft.

Doug. County Surveyors Office - James Byron, Deputy - Milo
Godfrey, Clete Putnam - July 1961 - C.S. File 49/67-15

Found - B.B.I. corner post rotted off and downhill.
Orig. NE BT, shows bark scribing "1/4S", now down.
B.B.I. now 16" Hemlock N.60°W., 11.9 ft., shows
scribe marks.
Set Brass cap mkd: County Surveyor's Office, 1961 1/4 S14|S13
T28S R4W
Set BBI's post alongside brass cap.
New BT - 10" R.Fir bears N.75°E., 23.4 ft. scribed 1/4 S13 CSBT

BLM resurvey by John M. Jelley under Group #570 - Survey,
June/July 1965 (DCSO records, Vol. 33 Pages 13936-37)

Found 1/4 sec. cor. as perpetuated and recorded by Byron in
1961, monumented with an I.Post 1" dia., firmly set,
extending 12" above ground with properly mkd. brass cap.
from which the remaining original bearing tree
A down Fir 48" dia., bears N.35°E., 60 lks. dist., with
fragmentary scribe marks visible on bark blaze.
and a bearing tree marked by Byron
A Fir 11" dia., bears N.75°E., 36 lks. dist., with frag-
mentary scribe marks visible on partly healed double
blaze.
and a bearing tree of which I have no record
A Hemlock 18" diam., bears S.55°W., 18 lks. dist., with
healed double blaze.
Add marks BLM 1965 to brass cap.

continued next page

TOWNSHIP 28 RANGE 04 POINT IDENTIFIER # 600440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 13 and 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Dan Saily, Lone Rock Timber Co. - Crew: Brett Ragon, Ignacio Roman & Trevor Clemo - 12/2023 - M183-27

Found - 1961 Douglas Co. Surveyors Office brass cap and iron pipe (properly mkd). The monument is 1.1 ft. above ground. Corner lies on steep east facing slope.
5 ft. tall wood post with steel cap stamped with a "5" and a coffee can nailed to top lies approximately 2 ft. southerly of corner.
23" D.Fir bears S.49½°W., 14.9 ft. record per 1991 BLM line notes (S.49½° 15.2 ft/ 23 lks) with a well healed face. We re-tag
26" D.Fir bears N.73°E., 22.8 ft. record (N.75°E., 23.8 ft./36 lks) with BLM tag & well healed face.
New - 23" D.Fir bears S.14°E., 19.8 ft. We tag and scribe ¼ S13 BT.