

TOWNSHIP 28 RANGE 04 POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 11, 12, 13 and 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W.H. Byars, under contract # 376 dated Jan. 22, 1881 (DCSO rec. Vol. 13 Page 5618)

Set post for cor. to secs. 11, 12, 13 and 14, from which:
An Alder 12" dia., bears N.88°E., 79 lks. dist.
Fir 60" dia., bears S.2°E., 45 lks. dist.
Cedar 14" dia., bears S.55°W., 53 lks. dist.
Fir 60" dia., bears N.15°W., 35 lks. dist.

Ben B. Irving - Wit: R.L. Irving; J.R. Strouss; J. Moore - May 16, 1927 - C.S. File 37/53 and "old" cor. book, Pg. 181

One old BT standing, now a 60" Fir, S.7°E., 29.7 ft.
Another Fir, N.17°W., 23.1 ft. probably recorded as BT but not marked.
Found rotten Alder stump, N.80°E., 52.1 ft., checks with field notes.
Set Post for corner with BTs as follows:
Fir 60" dia., bears S.7°E., 29.7 ft. (OBT)
Fir 60" dia., bears N.17°W., 23.1 ft. (OBT)
Hemlock 18" dia., bears S.63°W., 103.0 ft.
Fir 60" dia., bears N.19°E., 70.3 ft.

Doug. County Surveyors Office - James W. Byron, Deputy - Milo Godfrey, Clete Putnam - July 18, 1961 - C.S. File 49/67-14

Found - 60" Fir S.7°E., 29.7 ft., bark scribed "S13T28S R4WBT". (Old scribing, probably original)
60" Fir N.17°W., 23.1 ft. bark scribed "S11", does not look like original scribing.
Square scribed stake lying on ground alongside corner, badly rotted.
Set Brass cap mkd: County Surveyor's

S11	S12
S14	S13

 T28S R4W
Office, 1961
New BTs -10" R.Cedar S.20°W., 39.0 ft. mkd. T28S R4W S14 CSBT
12" Maple N.55°W., 10.4 ft. mkd. T28S R4W S11 CSBT.
8" Hemlock S.76°E., 38.7 ft. mkd. T28S R4W S13 CSBT.
12" Alder N.59°E., 20.9 ft. mkd. T28S R4W S12 CS BT.
Corner lies approx. 15 ft. N. of small creek flowing East.

Found OK, May 7, 1988, Ronald Geisler, C.S. File 63/60-2

BLM resurvey by John M. Jelley under Group #570. Survey, June/July 1965 (DCSO records, Vol. 33 Pages 13937-38)

Found cor. as perpetuated and recorded by James W. Byron, in 1961, monumented with an iron post 1" dia., firmly set, extending 12" above ground, with brass cap marked: (cont)

TOWNSHIP 28 RANGE 04 POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 11, 12, 13 and 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

COUNTY SURVEYORS OFFICE

T 28 S R 4 W

S 11 | S 12

S 14 | S 13

1961

from which the remaining original bearing trees

A Fir 60" dia., bears S.7°E., 45 lks. dist., with scribe marks S13 T28S R4W BT visible on bark blaze. (Rec. S.2°E.)

A Fir 62" dia., bears N.15°W., 35 lks. dist., with scribe marks S11 visible on bark blaze.

and bearing trees marked by Byron

An Alder 13" dia., bears N.59°E., 32 lks. dist., with scribe marks T28S R4W S12 CS BT visible on partly healed blaze.

A Hemlock 9" dia., bears S.76°E., 58 lks. dist., with scribe marks T28S R4W S13 CS BT visible on partly healed double blaze.

A Cedar 10" dia., bears S.18½°W., 59 lks. dist., with scribe marks T28S R4W S14 CS BT visible on partly healed blaze.

A Maple 12" dia., bears N.55°W., 15 lks. dist., with scribe marks T28S R4W S11 CSBT visible on partly healed blaze.

Add marks BLM 1965 to brass cap.