TOWNSHIP 28 RANGE 04 POINT IDENTIFIER # 603700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 35 and 36 only, T27-4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Contract #56 dated March, 1855 (DCSO Records, Volume 12 Page 5048)

Set sec. post, from which
A Maple, 5" dia. bears N.25°E., 20 lks. dist.
A Fir 10" dia. bears S.80°E., 22 lks dist.
A Fir 6" dia. bears S.57°W., 33 lks. dist.
A Fir 24" dia. bears N.58°W., 42 lks. dist.

Exteriors as surveyed by W.H. Byars, Under contract #376 dated January 22, 1881 (DCSO Records, Volume 12 Page 5081)

Sec. Cor. to secs. 2, 1, 35, and 36. Set new post as per instructions, bearing trees all standing (as per Flint, 1855)

James W. Byron, Deputy Co. Surveyor; Dale McFarland; Jim Powell - Sept. 14, 1961 - C.S. File 49/67-33

Found - Orig. 6" now 30" R.Fir S.57°W., 21.8 ft.
Orig. 24" now 30" R.Fir N.58°W., 27.7 ft. shows good bark scribing.
NE & SE BTs, now 30" Firs, show good bark scribing. Now down slope about 50 ft. Stump holes check bearing & distances. NE BT not a Maple.
Set brass cap mkd: County Surveyors Office, 1961 S 35 | S 36 T27S T28S R4W
New BT - 16" R.Fir bears N.47°E., 57.3 ft. scribed S36 T27S R4W CS BT.

Found OK by D.Edwards, 4/2001 - M138-8 & 65/34-6A & B
Fd. Ok by D. Edwards, 7/2010 - C.S. File 65/69-46
Fd as per record by D. Edwards, 10/2022 - C.S. File 65/110-7