TOWNSHIP 28 RANGE 04 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 Cor. to Sec's 25 & 36.

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W.H. Byars, under contract # 376 dated Jan. 22, 1881 (DCSO rec. Vol. 13, Pg. 5616)

Set Fir post for corner from which:
A Fir, 24" dia. bears S.15°W., 40 lks. dist.
A Fir, 6" dia. bears N.72°W., 45 lks. dist.

Doug. County Surveyors Office - James W. Byron Deputy. Dale McFarland, Jim Powell -Aug-Sept 1961. C.S. File no. 49/67-24

Found - Orig. 24" now 36" Fir, bears S.15°W., 26.4', shows good bark scribing '¼S BT'.
Orig. N.W. BT not found.

Set - Brass Cap at corner mkd: T28S R4W
¼ S 25 / S 36
County Surveyor's Office
1961

New BTs - 9" Cedar, bears N.75°W., 21.2' mkd: ¼ S25 CS BT.
7" R.Fir, bears S.31°E., 17.5' mkd: ¼ S37 CS BT.

Ken Hoffine - For: Lone Rock Timber Co - July 2020 - M177-20

Found - 1961 county cap (set by Byron 1961)
22" I.Cedar bears N.76°W., 21.0 ft (record N.75°W., 21.2 ft). Well healed face and tag

New - 17" I.Cedar bears S.39°E., 10.9 ft we scribe ¼ S36 BT and tag
13" D.Fir bears S.54°W., 13.9 ft we scribe ¼ S36 BT and tag
9" I.Cedar bears N.78½°E., 21.5 ft we scribe ¼ S25 BT and tag

Note - Corner monument is 0.5 ft above ground level and lies on bench on north facing slope approx 800 ft north of gravel logging road