

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 24 and 25

Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - W.H. Byars, under contract # 376 dated Jan. 22, 1881 (DCSO rec. Vol. 13 Page 5617)

-----  
 Set Post for ¼ sec. cor., from which  
 Laurel 10" dia., bears N.35°E., 40 lks.  
 Fir 24" dia., bears S.75°W., 25 lks.

BLM resurvey by Zirpel and Glenn under Special Instructions dated August 29, 1957 (DCSO records, Vol. 29 page 12226)

-----  
 Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.  
 Set a iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd: T28S R4W

¼  $\frac{S\ 24}{S\ 25}$   
 1958

from which

A Fir 19" dia., bears N.83¼°W., 93 lks. dist., marked ¼ S24 BT.

A Fir 8" dia., bears S.12 ¾°W., 32 lks. dist., marked ¼ S25 BT.

Ken Hoffine - For: Lone Rock Timber Co - Jan. 2020 - C.S. File 65/105-4

-----  
 Reset - 1958 BLM brass cap to 0.4 ft. above ground.  
 18" snag bears N.82½°W., 61.2 ft (1957 record N.83¼°W., 61.38 ft.) healed face.  
 10" snag bears S.14°W., 21.0 ft (1957 record S.12¾°W., 21.1 ft.) healed face.

New - 13" D.Fir bears S.69¾°W., 7.6 ft we scribe T28S R4W ¼ S25 BT and tag tree.

8" D.Fir bears N.41½°E., 11.0 ft we scribe ¼ S24 BT and tag.

Set - 5/8X40" iron rod with orange cap bears S.89°42'W., 17.6 FT

5/8X40" iron rod with orange cap bears N.63°34'E., 67.2 ft corner lies on west facing slope approx 10' from cat road on steep grade.

Note - BTs are blazed and scribed at the root crown with distances measured to a nail at the side center of the tree. the blazed faces of the bearing trees are painted fluorescent red and a bearing tree tag is nailed to the tree.