

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 13

Alias	Description

BLM survey, subd. of sec. 13 by James Jelley, under Group #570 - Survey June/July 1965 (DCSO records Vol. 33 Pg 13943)

Point for the center ¼ sec. cor. of sec. 13, at intersection with the E. and W. center line.

Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd: T 28 S R 4 W
C ¼ S 13
1965

from which

A Fir 7" dia., bears S.19°E., 98 lks. dist. mkd.
C ¼ S13 BT.

A Fir 28" dia., bears S.39°W., 50 lks. dist., mkd.
C ¼ S13 BT.

Douglas Co. Surveyors Office - John Pike - Stephen J. Flause
- 12/3/2007 - C.S. File 67/24-52

Found - 3" dia., brass cap, properly mkd, firmly set on 2½" O.D. iron post, projects 4" above ground.
28" now 28" dia., x 4 ft. tall rotting fir stump, fully healed single blaze vis bears S.39°W., 33.0 ft. Agrees w/rec.

7" now 14" dia., x 2 ft. tall snapped off fir stump tag visible on snapped off top alongside, stump bears S.19°E., 64.7 ft. agrees w/rec.

New - 5" dia., D.Fir, pistol butt, double blazed & scribed "X" on high blaze & "CS BT" on low blaze, bears S.81°W., 13.4 ft.

6" dia., D.Fir double blazed & scribed "C¼ S13 CS BT" bears N.6°E., 15.1 ft.

19" dia., I.Cedar double blazed & scribed "C¼ S13 BT" bears S.69½°E., 46.7 ft.

14" dia., D.Fir double blazed & scribed "C¼ S13 CS BT" bears N.73°E., 21.7 ft.

No suitable trees in NW quadrant.

Note - Corner lies in dense underbrush of area that has previously burned on gentle south facing slope. Compass decl. 16¼°E.