

TOWNSHIP 28 RANGE 04 POINT IDENTIFIER # 640500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 12 and 13

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - W.H. Byars, under contract # 376 dated Jan. 22, 1881 (DCSO rec. Vol. 13 Page 5619)

-----  
Set post for ¼ sec. cor, from which  
Fir 22" dia., bears S.18°W., 17 lks. dist.  
Fir 16" dia., bears N.80°W., 20 lks. dist.

Ben B. Irving - Wit: R.L. Irving; J.R. Strouss; J. Moore  
May 16-17, 1927 - C.S. File 37/53 and "old" cor. Book, Page 181

-----  
Identified by one OBT properly marked. Original notes call for two Firs. Found one Hemlock, N.10°W., 20 lks.  
Set Post for corner. New BTs as follows:  
Yew 10" dia., bears N.83°W., 20.9 ft.  
Cedar 15" dia., bears S.69°W., 56.8 ft.

Doug. County Surveyors Office - James W. Byron, Deputy - Milo Godfrey; Clete Putnam - July 21, 1961 - C.S. File 49/67-12

-----  
Found - Orig. 16" now 30" Fir stump N.80°W., 13.2 ft.  
Orig. SW BT, now shell of snag.  
Also find BBI's now 26" Cedar, S.69°W., 56.8 ft., previously opened, shows good scribing "¼ S13 CS".

We do not find BBI's NW BT.  
Set Brass cap at cor. & at East edge of 30" Fir log marked:  
County Surveyor's Office, 1961

¼  $\frac{S\ 12}{S\ 13}$

T 28 S R 4 W

New BT - 12" Yewwood bears N.82½°W., 20.3 ft. scribed ¼ S12 CS BT.

BLM resurvey by John M. Jelley, under Group #570, Survey June/July 1965 (DCSO records, Vol. 33 Pages 13938-39)

-----  
Found ¼ sec. cor. as perpetuated and recorded by Byron in 1961 monumented with an I.P. 1" dia., firmly set extending 16" above ground with properly mkd. Brass cap. from which the original bearing trees:

A Hemlock 30" dia., bears N.80°W., 25 lks. dist., with scribe marks ¼ S vis. on open blaze. (Rec. Fir 20 lks.)

The burned shell of a Fir 48" dia., bears S.18°W., 22 lks. dist., no marks remaining. (Rec. 17 lks.)

and bearing trees mkd. & recorded by Irving, in 1921:  
(Cont. Next Page)

TOWNSHIP 28 RANGE 04 POINT IDENTIFIER # 640500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 12 and 13

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A down Yew 13" dia., bears N.82½°W., 31 lks. dist., with scribe marks ¼ S12 CS BT visible on partly healed double blaze.

A Cedar 28" dia., bears S.70°W., 86 lks. dist., with scribe marks ¼ S13 CS visible on partly healed double blaze.

and a new bearing tree

A Cedar 12" dia., bears N.22½°W., 49 lks. dist., marked ¼ S12 BT.

Add marks BLM 1965 to brass cap.