

TOWNSHIP 28 RANGE 04 POINT IDENTIFIER # 641700

PRIMARY CORNER DESCRIPTION South ¼ Corner for Sec. 36, T27-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>Original - Nathaniel Ford, Contract #44 dated May 30, 1854 (DCSO records, Volume 12 Page 5045)</p> <p>-----</p> <p>Set ¼ sec. post, from which A R.Fir 30" dia. bears N.3°W., 13 lks. dist. A R.Fir 24" dia. bears S.3°E., 13 lks. dist.</p>
<p>Remeasurement and survey, by Addison R. Flint, Contract #56 dated March 1, 1855 (DCSO records, Volume 12 Page 5048)</p> <p>-----</p> <p>Set ¼ sec. post, from which A Laurel 14" dia. bears N.3°W., 13 lks. dist. A Cedar 8" dia. bears S.35°W., 35 lks. dist.</p>
<p>Exteriors by W.H. Byars, Contract #376 dated January 22, 1881 (DCSO records, Volume 12 Page 5081)</p> <p>-----</p> <p>Orig. sec. cor., set new post as per instructions, bearing trees all standing viz: A Laurel 14" dia. bears N.3°W., 13 lks. dist. A Cedar 8" dia. bears S.35°W., 35 lks. dist.</p>
<p>Douglas Co. Surveyors Office - James Byron; M. Godfrey; C. Putnam - July 13, 1961 - C.S. File 49/130-19</p> <p>-----</p> <p>Found - Orig. 8" now 16" Cedar snag S.35°W., 23.1 ft. We open & find good scribing on old chip "¼ S". No trace of Orig. NW BT found. Set brass cap at corner & under 36" log, mkd: South ¼ S36 T27S R4W, County Surveyor's Office, 1961. New BTs - 10" Cedar bears N.9°W., 9.7 ft. scribed S ¼ S36 CS BT. 12" Cedar bears N.59½°E., 49.0 ft. scribed S ¼ S36 CS BT.</p>
<p>David Edwards - For: Seneca Jones Timber Co. - 7/2010 - C.S. File 65/69-46</p> <p>-----</p> <p>Found - DCS Brass cap (In good condition) 24" Cedar W/healed blaze brs. N.59½°E., 49.0' New BT - Scribed "T27S R4W S36 BT" bears N.23°E., 38.2'. Set - 6 ft. steel post 2' East.</p>