

TOWNSHIP 28 RANGE 04 POINT IDENTIFIER # 700603

PRIMARY CORNER DESCRIPTION CC Cor. Secs. 6 & 7 only, T28-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - William N. Gibbs, under Contract #783 dated Dec. 3, 1908 (DCSO records, Vol. 13 Page 5595)

-----  
At point 3.28 chs. N.1°21'W. of cor. secs. 1 and 12,  
Set Cedar stake, 3 ft. long, 4" sq. 24" in the ground for  
closing corner secs. 6 and 7 marked CC T28S R3W on E.; S6 on  
N.; and S7 on S. face with 5 grooves on S. and 2 groove on N.  
face, from which

A Fir 11" dia., bears N.40°E., 39 lks. dist., mkd.  
T28S R3W S6 BT.

A Cedar 18" dia., bears S.84°E., 24 lks. dist. mkd.  
T28S R3W S7 BT.

Doug. County Surveyors Office - James Byron, Deputy - Milo  
Godfrey; Clete Putnam - July 1961 - C.S. File 49/67-13

-----  
Found - Both original BTs. Each tree is in good condition,  
each shows good scribing and each checks record.

Set Brass cap at cor. mkd: County Surveyor's CC S6 T28S R3W  
Office, 1961 R4W S7

No new BTs. Corner is under 30" log.

Ted Baker - For: Seneca Jones Timber Co. - May 2001 - M138-15

-----  
Found - 1961 Douglas Co. 2½" brass cap 0.89' east of line.

New BTs- 8" Fir N.14°E., 30.3'

4" Fir, S.78°E., 8.7'

All new BTs are scribed & painted red, distances to  
BTs are center measure.