

TOWNSHIP 28 RANGE 04 POINT IDENTIFIER # 700700

PRIMARY CORNER DESCRIPTION NE Cor. Sec. 1

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, Contract #44 dated May 30, 1854
(DCSO records, Volume 12 Page 5045)

Set a post, cor. of secs. 1 & 6, from which
A Laurel, 10" dia. bear S.55°E., 37 lks. dist.
A Laurel, 6" dia. bears S.55°W., 10 lks. dist.

Resurvey Exteriors by W.H. Byars, under Contract #376 dated
January 22, 1881 (DCSO records, Volume 13 Page 5528)

Intersect old corner 76 links W. Set post for cor. of T.28 S.
Rs. 3 and 4 W., from which
A Fir tree 40" dia. bears S.65°W., 24 lks. dist.
A Fir tree 60" dia. bears S.80°E., 30 lks. dist.

Douglas Co. Surveyors Office - Milo Godfrey, Clete Putnam
July 13, 1961 - C.S. File 49/130-20

Found - Both orig. BTs:
Orig. 60" now 66" Fir S.80°E., 19.8 ft., shows old
bark scribing "B 8".
Orig. 40" now 44" Fir S.85°W., (not S.65°W) 15.8 ft.
shows old bark scribing "S T".
Set brass cap at cor. mkd. CC S36 T27S County Surveyor's
R4W S 1 S 6 T28S R3W Office 1961
New BTs - 15" Cedar bears S.67°E., 23.8 ft. scribed S 6
T28SR3W CS BT.
6" R.Fir bears S.56°W., 33.6 ft. scribed S 1 CS BT.
(Sketch in CS file shows corner to be N.86½°W., 52.01 ft. from
corner for Sec. 36 and Sec. 31)

Found OK by T. Baker, May 2001 - M138-15