

TOWNSHIP 28 RANGE 05 POINT IDENTIFIER # 100200

PRIMARY CORNER DESCRIPTION Sec Cor for 30 & 31; 25 & 36 of T28-6

| Alias | Description |
|-------|-------------|
| _____ | _____ |
| Alias | Description |
| _____ | _____ |
| Alias | Description |
| _____ | _____ |
| Alias | Description |
| _____ | _____ |

Original - Elder and Gile, under Contract #31 dated April 7, 1853 (DCSO records, Vol. 13 Page 5648)

Set post corner to secs. 30, 31, 25 and 36, from which
A W.Oak 20" dia., bears S.65°W., 41 lks. dist.
A W.Oak 28" dia., bears N.25°W., 101 lks. dist.
A Y.Oak 8" dia., bears S.40°E., 63 lks. dist.
No tree near in sec. 30.

Doug. County Surveyors Office - James Byron, Deputy - Dale McFarland; Jim Powell - Sept/Oct. 1961 - C.S. File 49/64-12 (See also, Field Book 49 Pg. 42 for Cole corner)

Found - Orig. 20" now 28" W.Oak, shows good scribing on old face, "BT", S.65°W., 27.1 ft.
Orig. 28" now 32" W.Oak N.25°W., 66.7 ft. shows good scar. We do not open.
Orig. SE BT not found.

Set brass cap at cor. mkd:County Surveyor R6WS25|S30 T28S
Office, 1961 S36|S31 R5W

Note - At 4-way fence intersection. Cap set 2.0 ft. above ground. Solid rock at bottom.

New BTs - O.B.T. 28" W.Oak S.65°W., 27.5 ft. "S36 T28S R5W CS BT."
22" W.Oak bears S.41½°E., 43.0 ft. scribed S31 T28S R5W CS BT.
13" W.oak bears N.43°E., 45.7 ft. scribed S30 T28S R5W CS BT.
8" W.Oak bears N.31°W., 37.0 ft. scribed S25 T28S R6W CS BT.

Fd. OK by K.DeGroot, July 1999 - M133-3
Fd. OK by K.DeGroot, Dec. 2001 - 2001-0102 A&B

DCSO-GIS Corner visitation - 7/14/2004 - Typed: 2/1/2011 - C.S. File 67/33-1

Monument - BC/IP - 1.25"
Comment - OK