

TOWNSHIP 28 RANGE 05 POINT IDENTIFIER # 100440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 18; & 13 T28-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Elder and Gile, under Contract #31 dated April 7, 1853 (DCSO records, Vol. 13 Page 5646)

Set 1/4 sec. post, from which
 A Y.Oak, 20" dia., bears N.8°25'E., 1638 lks.
 A boulder 8 ft. x 5 ft. x 3 ft. high on top of ridge,
 bears S.15 3/4°W., 630 lks.

Kris DeGroot - For: Smith Trust - 6/2014 - M166-12

Restored from an orig. bearing object by Elder & Gile in 1853
 Set - A 1 1/4"x30" iron post, 6" below the ground, with a 2 1/2"
 brass cap mkd:

DOUGLAS COUNTY SURVEYOR

T28S

		1/4	
R			R
6	S13		S18 5
W			W

2014

From which the original 1853 bearing object by Elder & Gile:
 A boulder, 8'x5'x3' high, bears S.15°45'W., 415.80 ft
 (630 lks) - No mks visible.

Set - A 6" cotton-gin spike in top center of boulder & BT tag
 on face.

New RMs -

5/8" iron rod per M47-34 bears S.54°38'11"E. 1086.25 ft
 A 3/4" iron rod per M7-29 bears S.14°16'37"W., 654.72 ft.

Set - A 5/8"x30" iron rod w/PC bears S.0°4'01"W., 633.47 ft.

Set - A 5"x8' treated wood post, 3' in ground, 2 ft North of
 corner with location tag

Corner falls in cow pasture, 52 ft. East of N-S fence line,
 on top of N-S ridge.