TOWNSHIP 28 RANGE 05 POINT IDENTIFIER # 139700

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. Sec. 31, T27-5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile - Contract #31, dated April, 1853

Set - ¼ Sec. post, (on top of ridge) from which
A W. Oak, 16" dia. bears N.27°E., 36 lks. dist.
A W. Oak, 14" dia. bears N.19½°W., 81 lks. dist.

On S.E.R.A. Project - Claude Crocker; J.H. Wolford; B.A. Lane; Arthur Boyer - Vol. 4 Pgs. 50-58 - 1934-37-38

Set from original bearing trees by driving 3/4" x 36" round iron bolt for corner. Marked new bearing trees as follows:
Forked Fir 14" dia. bears N.56°E., 18.6 ft.
White Oak 16" dia. bears N.52°W., 20.5 ft.

Douglas County Surveyors Office - James Byron & crew November 1961 - C.S. 49/64-38

Found - 3/4" iron bolt at corner. NW BT shows good scars. I do not open. NE BT, now dead, 18" Fir. We open & find good scribing.
New BT - 8" W.Oak bears N.38°E., 16.2 ft. scribed S¼ S31 CS BT.

Found OK by H. Pieske June, 1982, M 90 - 22 and
Found OK August, 1990, M 112 - 12

Douglas Co. Surveyors Office - John Pike - Stephen J. Flause - 4/22/2008 - C.S. File 67/25-42

Fd. Iron bolt & 2 live BTs

Fd. 3/4" iron bolt - 7/2022 J. Estabrook - 2022-0035