

TOWNSHIP 28 RANGE 05 POINT IDENTIFIER # 140500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 7 & 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder and Gile, under Contract #31 dated April 7, 1853 (DCSO records, Vol. 13 Page 5678-9)

Set 1/4 sec. post, from which
A W.Oak, 6" dia., bears N.29°E., 119 lks.
A Y.Oak, 15" dia., bears S.44 1/4°W., 85 lks.

Kris DeGroot - For: Smith Trust - 6/2014 - M166-12

Restored from an original BT by Elder & Gile in 1853.
Set - A 1 1/4"x30" iron post, 24" in the ground w/18" stone collar to top, with a 2 1/2" brass cap mkd:

DOUGLAS COUNTY SURVEYOR
T28S R5W
1/4 $\frac{S 7}{S18}$
2014

From which an original BT by Elder & Gile in 1853:
A 17" B.Oak snag, 7' tall, bears N.29°E., 78.54 ft (119 lks) Steve Flause, DCSO, opens & finds fragmentary scribe and reverse mks.

New BTs -
A 14" W.Oak bears N.32°45'E., 15.5 ft scribed "1/4 S7 CS BT".
A 10" B.oak bears S.24°45'E., 9.0 ft scribed "1/4 S18 CS BT".

NEW RMs -
A 5/8"x30" iron rod w/1.5" DCSO alum cap mkd: "BO 1" bears S.54°15'58"W., 15.57 ft.
A 5/8"x30" iron rod w/1.5" DCSO alum cap mkd: "BO 2" bears N.23°52'59"W., 19.16 ft.