

TOWNSHIP 28 RANGE 05 POINT IDENTIFIER # 177700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 31 & 32, T27-5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set post for corner from which
 A maple 13" dia. bears N.38°E., 46 lks. dist.
 A fir, 15" dia. bears N.70 3/4°W., 99 lks. dist.

On S.E.R.A. Project - Claude Crocker; J.F. Wolford; B.A. Lane; Arthur Boyer - Vol. 4 Pgs. 50-58 - 1934-37-38

Found - One Original BT, other gone.
Set - Corner from one BT by driving 3/4" x 36 round iron bolt for corner from which
 Fir, 24" dia. bears N.9°E., 11.4 ft. New BT.
 Fir, 30" dia. bears N.70°45'W., 65.3 ft. Old BT.

James W. Byron & Crew - November, 1961 - C.S. 49/64-53

Found - I. Bolt & now 28" R. fir, N.9°W., NOT N.9°E. 11.4'.
Original NW BT down.
New BT - 21" R. Fir bears West, 5.5 ft. scribed S31 T27S R5W
C.S.BT.
 31/32 77.2'
 20' →→→ N.87°W 6/5
 --x---x-----x-----x-----x-----x

Found OK - August, 1990, M 112 - 12
Found OK by C. Sweeden, April 2004 - M144-56

Douglas Co. Surveyors Office - John Pike - Stephen J. Flauser -
4/28/2008 - C.S. File 67/25-42

Fd. OK as per rec.