

TOWNSHIP 28 RANGE 05 POINT IDENTIFIER # 200100

PRIMARY CORNER DESCRIPTION Sec. Cor. 31 & 32; 5 & 6, T29-5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Elder and Gile, under Contract #31 dated April 7, 1853 (DCSO records, Vol. 13 Page 5652)

Set post corner to secs. 31, 32, 5 & 6, from which
A W.Oak 12" dia., bears S.30°W., 19 lks. dist.
A Y.Oak 20" dia., bears N.2 3/4°W., 88 lks. dist.
A Y.Oak 24" dia., bears N.76½°E., 210 lks. dist.
A W.Oak 6" dia., bears S.70°E., 59 lks. dist.

Frank Cain, Surveyor - Oct. 1920 - Field Book 107 Page 40
(Recorded by F.C. Frear "old" cor. book Page 104)

Set post. Remark Oak in Sec. 31, C.S.
Renewals - A B.Oak 18" bears N.84 3/4°W., 58 lks. CS
A B.Oak 8" bears N.67½°E., 14½ lks, CS

Sam Whitset; H.L. Eppstein, (Record source not found)
Recorded in "old" corner book, Page 104

Set 3/4" x 30" G.I.P.
Marked trees
B.O. 15" N.81°W., 75 lks.
B.O. 36" N.8°W., 93 lks.
B.Oak 8" N.67½°E., 14½ lks.
W.O. 18" S.31°W., 19 lks. Old tree.

Doug. County Surveyors Office - James Byron, Deputy - Dale McFarland; J. Powell - Sept/Oct. 1961 - C.S. File 49/64-15

Found - 3/4" I.P. at corner and NE & NW BTs. as recorded.
SW BT gone.
New BT - 11" Laurel bears S.44°E., 6.5 ft. scribed T29S R5W
S5 CS BT.
No trees near to Southwest.

Doug. County Surveyors Office - Clell Goodwin, Deputy - Gary Langlitz; Vic Cangie; Lenora Ladig - 12/2/1975 C.S 57/39-22

Found - 3/4" x 28" I.P. at corner. From which
A Madrone, the main trunk of which is 11" in dia.,
bears S.44°E., 6.5 ft.
A 14" B.Oak bears N.70°E., 10.0 ft. (Rec. N.67½°E.,
9.6 ft.)
25" B.Oak bears N.81½°W., 51.0 ft. (Record N.81°W.,
49.5 ft.)

Calls appear to have been to the scribed face.
At Cor. we set a 1" x 30" I.P. with brass cap stamped:
continued next page

TOWNSHIP 28 RANGE 05 POINT IDENTIFIER # 200100

PRIMARY CORNER DESCRIPTION Sec. Cor. 31 & 32; 5 & 6, T29-5

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Note - We set and measured to spikes in the base of all bearing trees; bearings to the trees are based on our 2005 survey referenced hereon.

Corner lies at the intersection of East-West and South running fence lines on a southerly slope and north of road.