

PRIMARY CORNER DESCRIPTION Sec. Cor. 29, 30, 31 & 32

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - Elder and Gile, under Contract #31 dated April 7, 1853 (DCSO records, Vol. 13 Page 5672)

-
- Set post corner to secs. 29, 30, 31 and 32, from which
- A Y.Oak 10" dia., bears S.78°E., 31 lks. dist.
 - A Y.Oak 20" dia., beas S.78°W., 26 lks. dist.
 - A W.Oak 8" dia., bears N.14½°W., 78 lks. dist.
 - A Y.Oak 10" dia., bears N.72°E., 36 lks. dist.

John H. Markham, Jr. Wit: R.G. Boyd - For: Stomar Lbr. Co. Jan.20, 1958 - C.S. File 42/325

-
- Found - 13" W.Oak bears N.16°W., 51.5 ft. O.B.T. I rescribe S30 BT.
30" W.Oak windfall S.78°W., 17.2 ft. O.B.T., found scribe.
16" W.Oak windfall S.78°E., 20.5 ft. O.B.T.
- At corner point, set 1" x 30" I.P., from which
- 11" Laurel bears N.57°E., 17.7 ft. mkd. T28S R5W S29 BT.
 - 6" Laurel bears S.61°E., 17.0 ft. mkd. T28S R5W S32 BT.
 - 26" Laurel bears S.51°W., 46.0 ft. dist., fences run south and east.
- Creek bears West 170.0 ft.
Section corner for 31, 32, 5 & 6 bears South 5254 ft.
Center line County Road bears South 2055 ft.

Doug. County Surveyors Office - Larry E. Monrean, Deputy - Oct. 7, 1983 - C.S. File 62/9-16

-
- Found - 1" dia. I.P. set by Markham.
Orig. W.Oak 8" now 13" dia., bears N.16°W., 49.9 ft. (Orig. rec. N.14½°W., 51.5 ft.), reblazed by Markham, well healed. This tree is in a fence running west, fence wire grown in.
- 11" now 15" madrone, bark scribed and blazed bears N.57°E., 17.1 ft. (Rec. 17.7 ft.)
 - 6" now 12" Madrone, bark scribed & blazed bears S.61°E., 17.0 ft. The top is broken out of this tree, still growing.
 - 26" now 30" Madrone, scribing visible in partially healed blaze bears S.51°W., 46.0 ft.
- Set 1" x 30" I.P. with brass cap at position of found Markham monument. Monument protrudes about 12" above ground. Cap mkd:"Douglas Co Surveyors Office T28S S30 S29 S31 S32 R5W 1983". Place 1" I.P. along southerly edge of new monument. No new accessories.

continued next page

TOWNSHIP 28 RANGE 05 POINT IDENTIFIER # 200200

PRIMARY CORNER DESCRIPTION Sec. Cor. 29, 30, 31 & 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Fd. 5/91 by D. Baker, M 113-32
Found OK by N. Hibbs, May 2003 - M142-33
Greg Lang - Roseburg Resources - June 2005 - M148-4 & C.S. File 65/54-25A ----- Found - Brass Cap (properly marked) 14½" W.Oak bears N.15°W., 49.90' (orig. tree) 13½" Madrone bears S.58°E 16.65' (established in 1958 by John Markham) Also found a Madrone stump in Section 29 (this is the remains of a BT established in 1958 by John Markham) New - 7½" W.Oak bears N.68½°E., 36.70' scribed "T28S R5W S29 BT" 8" W.Oak bears S.78°W., 40.64' scribed "T28S R5W S31 BT" Note - We set and measured to spikes in the base of all bearing trees; bearings to the trees are based on our 2005 survey referenced hereon. Corner lies on a westerly slope East of a creek.