

TOWNSHIP 28 RANGE 05 POINT IDENTIFIER # 200240

PRIMARY CORNER DESCRIPTION 1/4 Cor. secs. 29 and 30

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Elder and Gile, under Contract #31 dated April 7, 1853 (DCSO records, Vol. 13 Page 5674)

Set ¼ sec. post, from which
A Laurel 7" dia., bears S.40°E., 13 lks. dist.
A Laurel 8" dia., bears S.66°W., 55 lks. dist.

Briggs, March 27, 1893 - for: Charles Fogg; Charles Blackman; Thomas Blackman - Vol. 1 Page 241

Set post marked BT -
Laurel, S.75°E., 44 lks.
Maple 6", West 11 lks.

Douglas Co. Surveyors Office - James Byron - Dale McFarland & John Powell - Oct. 1961 - C.S. File 49/64

Shown as not found on diagram found in C.S. File 49/64

Daniel Baker, PLS #1978 - For: Gerald Fisher - April 10, 1991 - M 113-32

Did not find original or Briggs corner.
Set 1½" x 36" iron pipe and brass cap mkd. with standard markings and PLS 1978.
New BTs -10" W.Oak N.30°E., 89.2 ft. scribed ¼ S29 BT.
8" double Madrone S.36°E., 75.9 ft. scribed ¼ S 29 BT.
5" Fir N.88°W., 90.2 ft. scribed ¼ S30 BT.
18" Fir N.57°W., 134.9 ft. scribed ¼ S30 BT.