

TOWNSHIP 28 RANGE 05 POINT IDENTIFIER # 200300

PRIMARY CORNER DESCRIPTION Sec Cor 19, 20, 29 and 30

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Elder and Gile, under Contract #31 dated April 7, 1853 (DCSO records, Vol. 13 Page 5674)

-----  
Set post corner to secs. 19, 20, 29 and 30, from which  
A Y.Oak 16" dia., bears N.62 3/4°E., 209 lks. dist.  
A Y.Oak 20" dia., bears S.77°E., 547 lks. dist.  
A Y.Oak 18" dia., bears S.5½°W., 627 lks. dist.  
A Y.Oak 20" dia., bears N.65°W., 451 lks. dist.

Doug. County Surveyors Office - James Byron, Deputy - M. Godfrey; S. Bilow - Feb. 1958 - C.S. File 49/64-1

-----  
Found - B.Oak, now 44" dia. N.65°W., 297.7 ft. showing scar. Chipped tree open & found reverse imprint of "BT" scribe.  
30" Oak, dead and down, lies S.5½°W., approx. 414 ft. This tree has been chopped open previously and I found reverse imprint of scribing "R5W" on one piece.  
No evidence found of other two BTs.  
At corner set I.P. with brass cap stamped: S19|S20 T28S R5W  
County Surveyor's Office, 1958 S30|S31  
Blazed and scribed:  
24" W.Oak N.47°E., 265.9 ft. "T28S R5W S20 CS BT".  
No other trees near.

Found, May 1991, Daniel Baker, M 113-32

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 6/20/2000 - C.S. File 66/16-12A

-----  
Found - 1958 DCSO BC/IP protrudes 12" out of ground.  
20" now 47" dia., B.Oak with a previously opened unhealed blaze, bears N.65°W., 297.7 ft. OBT  
24" now down & burnt W.Oak, no marks visible, root hole agrees with rec. "N.47°E., 265.9 ft." 1958  
New - 5/8"x30" long iron rod with DCSO plastic cap is set in broken rock out crop bears N.89°W., 183.8 ft.  
5/8"x30" long iron rod with DCSO plastic cap is set in a E-N fence line North 141.0 ft.  
Highest point of a large rock outcrop bears S.4½°E., 414.8 ft., approx. 12 ft. high.

Found OK by K. DeGroot, April 2004 - M144-28  
Fd. Brass cap by Neil Hibbs, 1/2010 - M160-29