

TOWNSHIP 28 RANGE 05 POINT IDENTIFIER # 200400

PRIMARY CORNER DESCRIPTION Sec. Cor. 17, 18, 19 and 20

Alias 042050 Description Int. I SE cor. DIC #42
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder and Gile, under Contract #31 dated April 7, 1853 (DCSO records, Vol. 13 Page 5676)

Set post corner to secs. 17, 18, 19 and 20, from which
A W.Oak 11" dia., bears N.19°E., 17 lks. dist.
A Y.Oak 15" dia., bears S.25°E., 66 lks. dist.
A Y.Oak 15" dia., bears S.70°E., 49 lks. dist.
A Y.Oak 22" dia., bears S.56°W., 110 lks. dist.

G.A. McHenry, Deputy Co. Surveyor - Witnesses: P.D. Wolford; S.K. Bowden - Nov. 1922 (No record source found except "old" cor. book, Page 105)

I renewed this corner from one original BT, which was alive and in which the scribe marks were visible. Set an Oak post 4" x 4" x 20" and marked trees as follows:

W.Oak 24" dia., bears N.19°E., 17 lks.
B.Oak 20" dia., bears S.72°E., 50 ft.
W.Oak 16" dia., bears S.56°45'W., 49.8 ft.
B.Oak 10" dia., bears N.59°30'W., 89.2 ft.

(A 2" pipe and BTs mentioned on M 1-24 by Irving in 1945)

Doug. County Surveyors Office - James Byron, Deputy - Dale McFarland; J.Powell - Nov. 1961 - C.S. File 49/64-22

Found - 1½" I.P. at corner. BTs still standing but dead:
24" W.Oak N.19°E., 11.2 ft.
16" W.Oak S.56 3/4°W., 49.8 ft., fd. scribing.
Other BTs destroyed.

Set brass cap mkd: County Surveyor's T28S R5W S18|S17
Office, 1961 S19|S20

New BTs -8" W.Oak S.89°W., 54.3 ft. mkd: T28S R5W S19 CS
BT.
11" W.Oak N.33°W., 93.4 ft. mkd: T28S R5W S18 CS
BT.
7" W.Oak N.33°E., 98.0 ft. mkd: T28S R5W S17 CS
BT.
9" W.Oak S.42°E., 92.0 ft. mkd: T28S R5W S20 CS
BT.

Set yellow tag on fence post along Roberts Creek Road, approx. 410 ft. N. of corner.

Fd. Brass cap by Neil Hibbs, 1/2010 - M160-29

continued next page

TOWNSHIP 28 RANGE 06 POINT IDENTIFIER # 200400

PRIMARY CORNER DESCRIPTION Cor. Secs. 17, 18, 19, & 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Kris DeGroot - For: Smith Trust - 6/2014 - M166-12

Found - 1961 DCSO BC/IP & Accessories per 1961 rec. The
BC/IP is 18" above ground and severely leaning.
I remove and reference base at flanges and reset
with top projecting 6" above ground.