

TOWNSHIP 28 RANGE 05 POINT IDENTIFIER # 200700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 5 & 6 only, No.

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Elder & Gile, Contract #31 dated April, 1853  
-----  
Set post cor. to secs. 5 and 6, from which  
    A Fir, 16" dia. bears S.1°W., 16 lks. dist.  
    A Fir, 16" dia. bears S.65½°E., 56 lks. dist.

---

A. Boyer; N.E. Richadson - Nov. 20, 1937 (Record Source not found. "old" cor. book, Page 106)  
-----  
Found original BTs in good shape. Marked B.T. on bark.  
Drove ¾" x 36" round iron bolt for corner, from which  
    36" Fir bears S.65°30'E., 56 lks. Orig. BT.  
    16" Fir bears S.1°W., 16 lks. Orig. BT.

---

James W. Byron Crew - November 1961 - C.S. 49/64-53  
-----  
Found - Iron bolt & both BTs which show good scars.  
Set - Brass cap alongside I. Bolt mkd. County Surveyors  
      Office 1961  
            S6|S5 T28S R5W

---

Found OK by H. Pieske, June 1982, M 90 - 22

---

Douglas Co. Surveyors Office - John Pike - Stephen J. Flauser -  
4/22/2008 - C.S. File 67/25-42  
-----  
Fd. bolt, 1 live OBT, 1 snag.

---