

TOWNSHIP 28 RANGE 05 POINT IDENTIFIER # 240400

PRIMARY CORNER DESCRIPTION 1/4 Cor. secs. 17 and 20

Alias <u>042060</u>	Description <u>FSF Cor. Hutson DIC #42</u>
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Elder and Gile, under Contract #31 dated April 7, 1853 (DCSO records, Vol. 13 Page 5676)

Set $\frac{1}{4}$ sec. post, from which
A Y.Oak 15" dia., bears N.2°E., 126 lks. dist.
A Y.Oak 16" dia., bears South, 66 lks. dist.

Ben B. Irving, Co. Surveyor - Wit: Carey Bowman; French; Thomas - March 1945 - M 1-24; C.S. 38/42

Set corner by double proportional measurement. Set 1½" x 42" pipe 36" in ground and marked:
An Oak 8" dia., N.30°E., 96.5 ft.
An Oak 54" dia., S.64°E., 92.2 ft.

Doug. County Surveyors Office - James Byron, Deputy - Dale McFarland; J. Powell - Nov. 1061 - C.S. File 49/64-21

Found - 1½" I.P. at corner 6" above ground and both BTs.
We open SE BT and find good scribing.
Rescribe SE bearing tree " $\frac{1}{4}$ S20 CS BT".