

TOWNSHIP 28 RANGE 05 POINT IDENTIFIER # 277700

PRIMARY CORNER DESCRIPTION Sec. Cor. to 32 & 33, T27-5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Corner to Secs. 32 and 33, from which
A Fir, 14" dia. bears N.16°W., 18 lks. dist.
A Fir, 12" dia. bears N.42°E., 8 lks. dist.

Doug. Co. Surveyors Office - Gary L. Langlitz; P. Earle -
December 16, 1974 - C.S. 57/36-1

Found - Orig. 12" now 30" D.Fir, with scribing "R5W T27S
S33 CC" visible on prev. opened blaze.
WE do not find the remaining orig. BT. At the corner point
determined by the record bearing & distance from the above
noted original BT, N.42°E., 5.3 ft.

WE SET - 1" x 30" I.P. with brass cap attached marked:

T 27 S
COUNTY SURVEYORS OFFICE S 32 | S 33
1974 S 5
T 28S R5W

We mark the following new BT:

A 12" incense cedar bears N.24°W., 8.8 ft. scribed "T27S
R5W S32 CS BT" on a double blaze.

Note: See the attached letters concerning the scribing "CC"
found on the orig. BT. (CS. File 57/36)

Compass declination setting: 20°East.

Carl Sweeden - For: VIPS Industries INC - April 2004 - M144-56

Found - 1974 2½"BC, up 0.4', 0.7 NO. of E/W wire fence.
22" D.Fir stump, N.48°E., 5.3', open w/scribe vis.,
tag, 6.0 tall.

13" I.Cedar stump, N.24°W., 8.8', dbl blaze, scribe
vis. tag, 6.0 tall.

New BTs- 21" I.Cedar BT, S.20°E., 9.25', scribed "T27S R5W
S32|S33 BT", tag.

22" I.Cedar BT, S.53°W., 17.40', scribed "T27S R5W
S32|S33 BT", tag.