TOWNSHIP 28 RANGE 05 POINT IDENTIFIER # 300140

PRIMARY CORNER DESCRIPTION 1/4 Cor. secs. 32 and 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder and Gile, under Contract #31 dated April 7, 1853 (DCSO records, Vol. 13 Page 5665)

Set ¼ sec. post, from which
A W.Oak 10" dia., bears S.59°E., 20 lks. dist.
A W.Oak 12" dia., bears N.53°W., 66 lks. dist.

J.W. Cole -Witnesses: Smith, Stone & Jennings - Vol. 3 Page 86; Field Book 50 Page 34

I renewed this corner from the two original bearing trees which are alive and standing and which I identified by the scars, but I did not chop open.
I set an Oak post 4" x 4" x 40" for corner and made a mound of rock for corner.

Doug. County Surveyors Office - James Byron, Deputy - Dale McFarland; J. Powell - Sept/Oct. 1961 - C.S. File 49/64-16

Found - Mound of rocks & burned stake. Also a 6" x 2" x 18" stone 4" above ground. Also BTs as recorded. We open NW BT and find good scribing.
Set brass cap mkd: County Surveyors Office 1961 ¼ S32|S33
T28S R5W
New BTs -16" W.Oak bears S.44°E., 44.5 ft. scribed ¼ S33 CS BT.
14" W.Oak bears N.40°W., 46.0 ft. scribed ¼ S32 CS BT.
This side of Mt. in 1961 fire area. All trees may die near ¼ corner.

Found OK, Nov. 1987, D. Bentz, M 105-13 ABC