

TOWNSHIP 28 RANGE 05 POINT IDENTIFIER # 300300

PRIMARY CORNER DESCRIPTION Sec. cor. for 20, 21, 28 & 29

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Elder and Gile, under Contract #31 dated April 7, 1853 (DCSO records, Vol. 13 Page 5666)

Set post corner to secs. 20, 21, 28 and 29, from which
A Laurel 16" dia., bears N.67°E., 97 lks. dist.
A Y.Oak 15" dia., bears S.33°E., 114 lks. dist.
A Laurel 20" dia., bears S.12°W., 166 lks. dist.
A Fir 20" dia., bears N.65¼°W., 69 lks. dist.

Doug. County Surveyors Office - James Byron, Deputy; M. Godfrey; S. Bilow - Feb. 1958 - C.S. File 49/64-2

Found - Laurel tree, now 40" dia., S.12°W., 98.5 ft. (not 109.6 ft.) which has been chopped open several years ago, showing scribe marks on old face. I could make out an "8", also "S 29". (This tree lies up a 30° slope from corner, which could account for difference in distance.)

Fir tree, now 32" dia., N.65¼°W., 45.5 ft. We chopped this tree open to expose part of old face & scribe marks "S20". Ring count shows this to be an orig. BT.

No trace of other 2 BTs found.

At cor. set I.P. with brass cap mkd: S20|S21 T28S R5W
County Surveyors Office 1958 S29|S28

Bark scribe 35" D.Fir S.81°W., 67.5 ft. "T28S R5W S29 CS BT".
Blaze and scribe 16" D.Fir N.48½°E., 103.9 ft. "T28S R5W S21 CS BT".

Blaze & scribe 13" D.Fir S.60°E. 104.4 ft "T28S R5W S28 CS BT"