

TOWNSHIP 28 RANGE 05 POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION Sec Cor for 4, 5, 8 & 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Elder and Gile, under Contract #31 dated April 7, 1853 (DCSO records, Vol. 13 Page 5670)

Set post corner to secs. 4, 5, 8 and 9, from which
A Y.Oak 15" dia., bears N.25°W., 25 lks. dist.
A Y.Oak 18" dia., bears N.70°E., 75 lks. dist.
A Laurel 15" dia., bears S.24½°E., 131 lks. dist.
A Laurel 14" dia., bears S.10°W., 118 lks. dist.

Doug. County Surveyors Office - James Byron, Deputy - John Powell; Dale McFarland - Nov. 1961 - C.S. File 49/64-35

Found - Orig. 15" now 30" B.Oak N.25°W., 16.5 ft. We open and find good scribing "S".
Orig. NE BT, down and rotted.
Orig. SE and SW BTs, alive, but centers rotted, no scribing.

Set brass cap at cor. mkd: County Surveyors S5|S4 T28S R5W
Office, 1961 S8|S9

New BTs -14" W.Oak bears N.66°W., 47.0 ft. scribed S5 T28S R5W CS BT.
13" R.Fir bears S.12°W., 8.0 ft. scribed S8 T28S R5W CS BT.
18" R.Fir bears S.61½°E., 34.4 ft. scribed S9 T28S R5W CS BT.
9" W.Oak bears N.17°E., 36.9 ft. scribed S4 CS BT.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 9/2/99 - C.S. File 66/12-2

Found - A 2½" dia. brass cap (properly marked) on a 1½" O.D. x 36" long iron pipe approx. 10 ft. easterly from corner position and buried in a stump pile. 1961
13" now rotted D. Fir, roots no blazes or scribing found bears S.12°W., 8.0 ft. (agrees w/rec)1961
18" now 18" dia. rotted D. Fir stump with down tree, has a fully healed double blaze, bears S.61½°E., 34.4 ft. (agrees with record).1961
14" rotted 3 ft. tall Oak stump, reverse scribing found "CS BT" bears N.66°W., 47.0 ft. (agrees with record). 1961
14" now 20" dia. 4 ft. tall Madrone stump with a previously opened, rotted blaze with no scribing visible S.12½°W., 77.9 ft. (record S.10°W., 77.9 ft.) OBT

continued next page

TOWNSHIP 28 RANGE 05 POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION Sec Cor for 4, 5, 8 & 9

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Set - The 1961 DCSO BC/IP is set at a position as determined from the above found BTs. The marks "RESET 1999" are added to the brass cap. The monument now protrudes 6" above ground.

New BTs- 15" dia. P.Pine double blazed and scribed "T28S R5W S8 CS BT" bears S.70½°W., 44.5 ft.

11" dia. D.Fir double blazed and scribed "T28S R5W S8 CS BT" bears S.13°W., 79.9 ft.

17" dia. P.Pine single blazed and scribed "T28S R5W S5 CS BT" bears N.76°W., 67.3 ft.

17" dia. I.Cedar single blazed and scribed "T28S R5W S9 CS BT" bears S.36 3/4°E., 166.9 ft.