

TOWNSHIP 28 RANGE 05 POINT IDENTIFIER # 340500

PRIMARY CORNER DESCRIPTION 1/4 Cor. secs 9 and 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Elder and Gile, under Contract #31 dated April 7, 1853 (DCSO records, Vol. 13 Page 5669)

Set ¼ sec. post, from which
A W.Oak 10" dia., bears S.60½°E., 56 lks. dist.
A Y.Oak 16" dia., bears N.52°E., 272 lks. dist.

Ben B. Irving, Co. Surveyor - Wit: Carey Bowman; French; Thomas - March 1945 - C.S. File 38/42; M 1-24

Identified from Y.Oak N.52°E., (?) lks., chopped out but scribe marks legible. Original BT, a W.Oak S.60½°E., 56 lks., in place, in good shape and not chopped out but remarked.

New BT - An Oak 10", N.70°E., 29.2 ft. mkd. ¼ S9 CS BT.
Set in ¾" x 36" drill steel with post alongside.

Doug. County Surveyors Office - James Byron, Deputy - Dale McFarland; John Powell - Nov. 1961 - C.S. File 49/64-26

Found - Drill steel at corner, and now 12" W.Oak bears N.77°E., not N.70°E., 29.2 ft., shows good scars.

Orig. W.Oak bears S.56°E., not S.60½°E., 37.0 ft. now 29".

Corner bears S.70°W., 13.5 ft. from fence corner.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 9/8/1999 - C.S. File 66/12-17

Found - ¾" dia., axle protrudes 2" above ground. 1945 10" now 30" dia., W.Oak with 1945 remark a partially healed double blaze no scribing visible, bears S.57¼°E., 36.1 ft. (1961 rec. S.56°E., 37.0 ft., dist. fits well with slope) OBT

Remains of rotted Oak found at rec. "N.52°E., 179.5 ft." OBT

10" now 18" dia., W.Oak with a partially healed double blaze, faint illegible scribing visible bears N.77°E., 29.2 ft. (agrees w/1961 rec.) 1945

New BTs- 16" W.Oak in fence line scribed "¼ S9 BT" on high single blaze 4½ ft. above ground. bears N.17½°E., 3.7 ft.

Northern 11" dia., trunk of a triple trunked W.Oak, double blazed & scribed "¼ S16 CS BT" center base of north trunk bears S.42°W., 23.0 ft.

See CS file for sketch of fences