TOWNSHIP 28 RANGE 05 POINT IDENTIFIER # 400140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 33 & 34

Alias Description
Alias Description
Alias Description
Alias Description

Original - Elder and Gile, under Contract #31 dated April 7, 1853 (DCSO records, Vol. 13 Page 5657)

Set ¼ sec. post, from which
A Fir 36" dia., bears S.50°E., 9 lks. dist.
A Fir 18" dia., bears S.83 3/4°W., 186 lks. dist.

BLM resurvey by Bedell and Peterson, under Group #1425. Survey April, 1988-April 1990 (DCSO records, Vol. 49 Page 18708)

Corner determined from the remains of an original bearing tree:
A sawed Fir stump 28" dia., bears S.83 3/4°W., 186 lks. dist., with axe marks & a chaining notch on an open blaze.
At the corner point
Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd: T 28 S R 5 W
¼
S 33 S 34
1988
from which new bearing trees
A Fir 11" dia., bears S.75½°E., 55 lks. dist., mkd. ¼ S34 BT.
A Fir 13" dia., beas S.75¼°W., 82 lks. dist., mkd. ¼ S33 BT.
Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.