TOWNSHIP 28 RANGE 05 POINT IDENTIFIER # 400240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 27 and 28

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder and Gile, under Contract #31 dated April 7, 1853 (DCSO records, Vol. 13 Page 5656)

Set ¼ sec. post, from which
A Laurel 12" dia., bears S.58°E., 35 lks. dist.
A Y.Oak 12" dia., bears S.1°W., 47 lks. dist.

BLM resurvey by Peterson and Bedell under Group #1425. Survey April 1988-April 1990 (DCSO records, Vol. 49 Pages 18710-11)

Point for ¼ corner at proportionate distance; there is no remaining evidence of the original corner.
Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd: T 28 S R 5 W

¼
S 28 S 27
1988

from which
An Ok 17" dia., bears S.35½°E., 43 lks. dist. mkd, ¼ S27 BT.
An Oak 7" dia., bears S.61 3/4°W., 19 lks. dist., mkd. ¼ S28 BT.
Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

Found OK by W. Ruppert, April 2000 - M132-31