TOWNSHIP 28 RANGE 05 POINT IDENTIFIER # 400440

PRIMARY CORNER DESCRIPTION 1/4 Cor. secs. 15 and 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder and Gile, under Contract #31 dated April 7, 1853 (DCSO records, Vol. 13 Page 5655)

Set ¼ sec. post, from which
A W.Oak 18" dia., bears S.77°W., 30 lks. dist.
A W.Oak 16" dia., bears N.46°E., 7 lks. dist.

W.H. Woods - Wit: W.S. Crear; A.B. Hatfield; L.S. Patterson -Nov. 16, 1925 - C.S. File 3/28; Vol. 3 Page 235; "Old" corner book, Page 105.

Old bearing trees good. Set new stake.

Doug. County Surveyors Office - James Byron, Deputy - Dale McFarland; John Powell - Nov. 1961 - C.S. File 49/64-28

Found - Both orig. BTs, show good scribing on old faces, each checks bearing and distance.
Set Brass cap at cor. mkd: County Surveyor's Office, 1961
¼ S16|S15 T28S R5W
(Corner bears N.75°W., 23.0 ft. from 3-way fence corner.)
New BTs -8" R.Fir N.85°E., 38.2 ft. scribed ¼ S15 CS BT.
26" R.Fir, S.37½°W., 38.5 ft. scribed ¼ S16 CSBT.

Found OK, Donald Bentz, August, 1991, Partition, 1991-0065