

TOWNSHIP 28 RANGE 05 POINT IDENTIFIER # 440200

PRIMARY CORNER DESCRIPTION 1/4 Cor. secs. 27 & 34

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - A.R. Flint and L.L. Williams, under Contract #151 dated May 23, 1871 (DCSO records, Vol. 13 Page 5689)

Set post to ¼ sec. corner, from which
A Cedar 4" dia., bears N.58°W., 81 lks. dist.
A W.Oak 3" dia., bears S.35°W., 10 lks. dist.

BLM Cadastral resurvey by Bedell & Peterson, under Group #1425 - Survey, April, 1988-April 1990 (DCSO records, Vol. 49 Page 18709)

Point for ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd: T 28 S R 5 W

¼ S 27
S 34
1988

from which
A Fir 9" dia., bears S.58½°E., 14 lks. dist. ¼ S34 BT.
A Fir 20" dia., bears N.53 ¾°W., 41 lks. mkd. ¼ S27 BT.
Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

Douglas Co. Surveyors Office - John Pike - Kody Inda -
6/25/2008 - C.S. File 67/25-60

Fd. BLM BC & 2 BTs as per record.