

TOWNSHIP 28 RANGE 05 POINT IDENTIFIER # 440400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 15 and 22

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

Original - Elder and Gile, under Contract #31 dated April 7, 1853 (DCSO records, Vol. 13 Page 5682)

Set ¼ sec. post, from which
A Laurel 30" dia., bears N.72°E., 40 lks. dist.
A W.Oak 12" dia., bears S.12°W., 37 lks. dist.

W.F. Briggs, for John Hatfield - March 1893 - Volume 1 Page 237

Set post as per original BTs still standing, to wit:
Laurel 30", bears N.72°E., 40 lks.
W.Oak 12" bears S.12°W., 37 lks.

Ben B. Irving, D.C.S. - Wit: J.E. Pinkerton; R.L. Irving; Geo. Piper - July 5, 1939 (No record source found, see "old" corner book, Page 106)

Location identified from old stake from which a Laurel formally was N.72°E., 40 lks., now has tow large Laurels which has stooled out from the orig. tree and a W.Oak 30" dia., bears S.12°W., 37 lks. with blazes plain.
Set a post for the corner, from which
An Oak 8" dia., bears S.45°W., 38.6 ft.
An Oak 9" dia., bears N.68°E., 77.8 ft.

Doug. County Surveyors Office - James Byron, Deputy - M. Godfrey; S. Bilow - June 6, 1958 - C.S. File 49/64-5

Found - Scribed post out of ground near corner.
Orig. 10" now 24" W.Oak shows good scar. I do not open.
Orig. 30" now 48" Laurel, center rotted.
B.B.I. 8" now 12" W.Oak down, scribing visible S.45°W., 38.6 ft.
9" W.Oak now 12" N.68°E., 77.8 ft. shows good scar, I do not open.
Set Brass cap at cor. mkd. ¼ S15 T28S R5W County Surveyor's Office, 1958
S22
New BTs -8" R.Fir bears N.49°W., 15.0 ft. scribed ¼ S15 CSBT
7" W.Oak bears S.30°W., 42.2 ft. scribed ¼ S22 CSBT

Found OK, Nov. 1989, Donald Bentz, R.M. 3-75