TOWNSHIP 28 RANGE 05 POINT IDENTIFIER # 440500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 10 and 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder and Gile, under Contract #31 dated April 7, 1853 (DCSO records, Vol. 13 Page 5659)

Set ¼ sec. post, from which
A W.Oak 20" dia., bears N.62½°E., 51 lks. dist.
A W.Oak 28" dia., bears S.13½°E., 144 lks. dist.

W.H. Woods - Wit: W.S. Crear; A.B. Hatfield; L.S. Patterson Nov. 16, 1925 - C.S. File 3/28; Vol. 3 Page 235 and "old" corner book, page 105

Old bearing trees good. Set new stake.

Doug. County Surveyors Office - James W. Byron, Deputy - Dale McFarland; John Powell - Nov. 1961 - C.S. File 49/64-27

Found - Both original BTs, each was previously opened, centers now rotted. The SE BT shows some reverse scribe marks.
Set Brass cap at cor. mkd. County Surveyor's ¼ $\frac{S10}{S15}$ T28S R5W Office, 1961
New BTs -Rescribe orig., now 36" W.Oak N.62½°E., 36.0 ft. "¼ S10 CS BT"
8" W.Oak bears S.62°E., 46.9 ft. scribed "¼ S15 CS BT."
(See C.S. file for fence relationship to corner.)

Found OK, Donald Bentz, November 1989, RM 3-75
Fd. BC per 1961 ren. 9/2021 B. Knapp - M178-41