

TOWNSHIP 28 RANGE 05 POINT IDENTIFIER # 500140

PRIMARY CORNER DESCRIPTION 1/4 Cor. secs. 34 and 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint & L.L. Williams, Under Contract #151, dated May 23, 1871 (DCSO records Volume 13 Page 5687)

Set post to 1/4 sec. corner, from which
A Fir 20" dia., bears N.45°E., 82 lks. dist.
A Fir 36" dia., bears N.25°W., 19 lks. dist.

John H. Markham, Jr. Engineer - For: Stomar Lumber Co. - Geo. Vaughn, witness - Aug. 1950 - C.S. File 40/272-1

Determined from remains of old BT.
48" Fir snag bears N.53°E., 50.5 ft. scribe legible.
45" Fir stump bears N.37°W., 14.0 ft.
At corner point set 3/4" x 30" I.P. 15" in ground and made a pile or rocks, from which
A W.Oak 10" dia., bears N.86°W., 40.0 ft. mkd. 1/4 S.
S34 2880 BT.
A Fir 7" dia., bears N.74°E., 13.0 ft. mkd. 1/4 S35 2880 BT.

BLM resurvey by Peterson & Bedell under group #1425. Survey, April 1988-April 1990 - (DCSO records, Vol. 49 Pages 18702-03)

Corner perpetuated and recorded by John Markham in 1950, monumented with an iron pipe 1" dia., firmly set, projecting 15" above ground, from which the remains of the original bearing trees:

A root hole bears N.50 1/2°E., 79 lks. dist., with a down fir alongside, 50" dia., with scribe mark 1 visible on an opened blaze. (Rec. N.45°E., 82 lks.)
A rotted Fir stump size indeterminate, bears N.35 3/4°W 22 lks. dist., no marks remaining. (Rec. N.25°W., 19 lks.)
and the remains of the bearing trees mkd. by Markham
A Fir 22" dia., bears N.77°E., 21 lks. dist. with healed blaze.
An Oak snag 12" dia., bears N.86 1/2°W., 62 lks. dist., with healed blaze.

At the corner point
Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd: T 28 S R 5 W

1/4
S 34 | S 35
1988

from which a new bearing tree
A Fir 18" dia., bears S.45 1/2°W., 17 lks. dist. mkd.
1/4 S34 BT. (Cont. Next Page)

TOWNSHIP 28 RANGE 05 POINT IDENTIFIER # 500140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 34 and 35

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.