TOWNSHIP 28 RANGE 05 POINT IDENTIFIER # 500240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 26 and 27

Alias Description
Alias Description
Alias Description
Alias Description

Original - A.R. Flint and L.L. Williams under Contract #151 dated May 23, 1871 (DCSO records, Vol. 13 Page 5689)

Set post to ¼ sec. corner, from which
A Fir 8" dia.,b ears S.58°E., 12 lks. dist.
A Laurel 14" dia.,b ears S.30°W., 27 lks. dist.

BLM resurvey by Peterson & Bedell under Group #1425. Survey, April 1988-April 1990 (DCSO records, Vol. 49 Page 18705)

Point for the ¼ corner, at proportionate distance; there is no remaining evidence of the original corner.
Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd: T 28 S R 5 W

¼
S 27 S 26
1988

from which
A Fir 10" dia., bears N.54 3/4°E., 23 lks. dist., mkd. ¼ S26 BT.
AFir 14" dia., bears N.33°W., 55 lks. dist., mkd. ¼ S27 BT.
Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.