

PRIMARY CORNER DESCRIPTION Sec. Cor. for 22, 23, 26 & 27

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Original - A. L. Flint & L. L. Williams, under Contract #151 dated May 23, 1871 (DCSO records, Vol. 13 Page 5689-90)

-
- Set post to secs. 22, 23, 26 and 27, from which
- A Laurel 4" dia., bears N.18°W., 37 lks. dist.
 - A Laurel 4" dia., bears N.80°E., 30 lks. dist.
 - A Laurel 4" dia., bears S.35°E., 49 lks. dist.
 - A Laurel 4" dia., bears S.18°W., 40 lks. dist.

BLM resurvey by Bedell and Peterson, under Group #1425 Survey, April 1988-April 1990 (DCSO records, Vol. 49 Page 18706)

Point for the sec. cor. at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd: T 28 S R 5 W

S 22 S 23
S 27 S 26
1988

from which

- A Fir 4" dia., bears N.67¼°E., 104 lks. dist.
mkd. X BT.
- A Fir 8" dia., bears S.2½°E., 59 lks. dist. mkd.
T28S R5W S26 BT.
- A Fir 4" dia., bears S.53 3/4°W., 49 lks. dist.
mkd. X BT.
- A Fir 13" dia., bears N.32°W., 102 lks. dist., mkd.
T28S R5W S22 BT.

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

Fd. Ok by D.Edwards, 10/96, M 126-10.

Fd. Ok by D.Edwards, 3/2001, M 136-68