

TOWNSHIP 28 RANGE 05 POINT IDENTIFIER # 500500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 10, 11, 14 and 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder and Gile, under Contract #31 dated April 7, 1853 (DCSO records, Vol. 13 Page 5659)

Set post corner to secs. 10, 11, 14 and 15, from which
A W.Oak 15" dia., bears S.44½°E., 61 lks. dist.
A W.Oak 18" dia., bears N.22°W., 52 lks. dist.
A Y.Oak 12" dia., bears N.38°E., 117 lks. dist.
A Y.Oak 16" dia., bears S.88°W., 245 lks. dist.

Doug. County Surveyors Office - James Byron, Deputy - Dale McFarland; John Powell - Nov. 1961 - C.S. file 49/64-47

Found - Orig. 18" now 24" W.Oak snag, N.22°W., 34.3 ft. Old face rotted out.
Orig. 15" now 24" W.Oak S.44½°E., 40.3 ft., we open & find good scribing.
No other BTs found.

Set Brass cap mkd: County Surveyor's S10 | S11 T28S R5W
Office, 1961 S15 | S14

New BTs -7" W.Oak bears N.26°W., 45.7 ft. scribed S10 T28S R5W CS BT.
12" W.Oak bears N.30°E., 34.6 ft. scribed S11 T28S R5W CS BT.
42" B.Oak bears S.27°E., 77.7 ft. scribed S14 T28S R5W CS BT.
No trees near to SW.

Fd. BC per 1961 ren. 9/2021 B. Knapp - M178-41