TOWNSHIP 28 RANGE 05 POINT IDENTIFIER # 500540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 10 and 11

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder and Gile, under Contract #31 dated April 7, 1853 (DCSO records, Vol. 13 Page 5662)

Set ¼ sec. post, from which
A Y.Oak 10" dia., bears S.2½°E., 481 lks. dist.
A W.Oak 18" dia., bears S.67½°W., 191 lks. dist.

Doug. County Surveyors Office - James Byron, Deputy - D. McFarland; John Powell - Nov. 1961 - C.S. File 49/64-25

Found - Orig. 10" now down & rotted Oak, S.2½°E., 317.5 ft.
Orig. 18" now 24" Oak snag, shows reverse scribing on old face.
Set Brass cap at cor. mkd: County Surveyor's Office, 1961
¼ S10|S11 T28S R5W
New BTs -32" W.Oak bears S.42°W., 27.0 ft. scribed ¼ S10 CSBT
11" W.Oak bears S.71°E., 59.3 ft. scribed ¼ S11 CSBT
Corner under N-S fence.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 7/11/2002 - C.S. File 66/34-17

Found - 1961 DCSO brass cap/iron pipe, protrudes 13" out of ground, 1 ft. West of new N-S fence line.
18" W.Oak now fallen rotted Oak, root hole bears S.67½°W., 126.1 ft. (OBT)
32" now 47" dia, triple trunk W.Oak with a fully healed double blaze bears S.38°W., 27.0 ft. (Rec. S.42°W., 27.0 ft.) 1961
11" now 20" dia., W.Oak with a fully healed double blaze bears S.72½°E., 59.3 ft. (Rec. S.71°E., 59.3 ft.) 1961
New - 14" dia., W.Oak double blazed & scribed "¼ S10 CS BT" bears N.34°W., 64.0 ft.
21" dia., W.Oak double blazed & scribed "¼ S11 CS BT" bears N.32°E., 84.8 ft.
Compass decl. 17¼°E.

Found OK by H. Pieske, Dec. 2003 - M143-44
Fd. BC per 1961 ren. 9/2021 B. Knapp - M178-41