

TOWNSHIP 28 RANGE 05 POINT IDENTIFIER # 500600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 2, 3, 10 & 11

Alias 041020 Description NW Cor. Gilmore DIC #41
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder and Gile, under Contract #31 dated April 7, 1853 (DCSO records, Vol. 13 Page 5662)

Set post corner to secs. 2, 3, 10 and 11, from which
A Y.Oak 16" dia., bears S.9°W., 1445 lks. dist.
A Y.Oak 18" dia., bears S.16°E., 1668 lks. dist.
Made trench, no other trees near.

W. F. Briggs, D.C.S. - For: Ths. Boggs et al - Jan. 8, 1886
Volume 1 Page 70

Set rock, 22 x 10 x 8 by BT.

Doug. County Surveyors Office - James Byron, Deputy - For:
Douglas County - Jan. 29, 1962 - C.S. File 52/100 & M 23-5

Found - Orig. 16" now 30", down & rotted Oak, S.9°W., we
find good reverse scribing.

Orig. 8" now 16" Oak stump S.16°E., shows good
reverse scribing.

Set Brass cap along North side of corner fence post & mkd:
County Surveyor's

S 3	S 2
S 10	S 11

 T28S R5W
Office, 1962

No trees near.

Set - Stone 12" x 10" base, 18" high, 6" out of ground. Top
3" x 3". Chiseled + on top, bears N.36°E., 4.3 ft.

Stone, 10" x 6" base, 18" high, 4" out of ground, wedge
shape. Top 10" x 2". Chiseled + on North corner,
bears N.53½°W., 4.2 ft.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -
Stephen J. Flause - 7/17/2002 - C.S. File 66/34-20

Found - 1961 BC/IP and stones not found, area around corner
bulldozed.

Orig. 16" Y.Oak now rotted remains of Oak stump &
roothole bears S.14°36'48"E., 1111.5 ft. (1961
rec. S.14°40'40"E., 1111.5 ft. orig. rec.
S.16°E., 1100.9 ft.)

Orig. 18" Y.Oak now rotted remains of Oak bears
S.10°06'W., 933.8 ft. (orig. rec. S.9°W., 953.7
ft. 1961 rec. S.10°16'40"W., 933.8 ft.)

Checked 1961 tie to ¼ S2/S11 and agree with M23-5
survey record. (S.88°42'30"E., 2640.10 ft.)
Position of sec. corner as monumented in 1961
determined by survey M23-5 as shown above.

continued next page

TOWNSHIP 28 RANGE 05 POINT IDENTIFIER # 500600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 2, 3, 10 & 11

Alias 041020 Description NW Cor. Gilmore DIC #41
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Set - 2 3/8" dia., brass cap on a 1 1/4" O.D. by 30" long
iron pipe protrudes 7" out of ground mkd:

DOUGLAS CO. SURVEYORS OFFICE

T 28 S

R 5 W

S 3 | S 2

S 10 | S 11

2002

9" dia., Maple with fence wire grown into trunk
single blazed & scribed "X S11 BT" above fence
line approx. 5 1/2 ft. above ground. bears S.49°E.,
32.1 ft.

19" dia., Apple double blazed & scribed "X S10 CS
BT" bears S.16°W., 74.2 ft.

13" dia., Maple double blazed & scribed "T28S R5W
S10 CS BT" bears S.88°W., 66.1 ft.

7" dia., Apple double blazed & scribed "S2 CS BT"
bears N.14°E., 76.5 ft.

Compass decl. 17 1/4°E.

Found OK by H. Pieske, Dec. 2003 - M143-44

Fd. BC per 2002 ren. 9/2021 B. Knapp - M178-41