

TOWNSHIP 28 RANGE 05 POINT IDENTIFIER # 500700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 2 & 3; 34 & 35, T27-5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853 (DCSO records Vol. 12 Pages 5101-2)

Set post cor. to Secs. 2 & 3, from which
A G.Oak 26" dia. bear S.35°E., 82 lks. dist.
A G.Oak 24" dia. bears S.46°W., 52 lks. dist.

(DCSO records Vol. 12 Pages 5106)
To Cor. of Secs. 2 & 3, Tp. 28 S., R. 5 W. marked same
post as also cor. to Secs. 34 & 35, from which
A Y.Oak 10" dia. bears N.62½°E., 33 lks. dist.
A Y.Oak 20" dia. bears N.5°W., 57 lks. dist.

James W. Byron; Milo Godfrey; Clete Putnam
December 18, 1959 - C.S. 49/62-4

Found - Orig. 26" now 46" B.Oak, S.35°E., 54.1 ft. I open
& find good scribing "S".
Orig. 24" now large Oak stump S.46°W., 34.3 ft.
center rotted, no scribing.
Orig. 20" now 40" B.Oak, down, N.5°W., 37.6 ft.
Orig. 10" now 30" B.Oak, N.62½°E., 21.8 ft. I do
not open.

New BTs - 28" B.Oak, S.28½°W., 69.8 ft. scribed S 3 T28S
R5W CS BT.
46" B.Oak, S.33½°E., 55.0 ft. rescribed S2 T28S
R5W CS BT.
11" W.Oak, bears N.2°W., 59.9 ft. scribed S34
T27S R5W CS BT.

Set -Brass cap at corner mkd. County Surveyors Office 1959
S 34|S35 T27S
S 3|S 2 T28S R5W

Note: E-W fence 10 ft. north.

Found Ok, April 22, 1980

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -
Stephen J. Flause - 12/13/93 - C.S. File 64/50-15

Found - A 2½" dia., DCSO Brass Cap on a 1½" O.D. iron pipe
protruding 12" above ground. 1959
10" now 37" dia., B.Oak with fully healed blazes,
bears N.62½°E. 23.0' (Rec. N.62½°E. 21.8') OBT
26" now 36" dia., 10' high hollowed and burnt Oak
snag no blazes or scribing visible, bears
S.33½°E., 55.0' (Agrees with 1959 Ren.) OBT

(Cont. Next Page)

TOWNSHIP 28 RANGE 05 POINT IDENTIFIER # 500700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 2 & 3; 34 & 35, T27-5

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

No evidence of any other Orig. BTs found.
28" now 36" dia., B.Oak with a fully healed double
blaze bears S.28½°W. 69.8' (Agrees w/Rec) 1959
11" now 19" dia., W.Oak with a fully healed double
blaze, bears N.3½°W., 59.9' (Rec. N.2°W.,
59.9') 1959
New BT - 21" dia., W.Oak double blazed and scribed "T28S R5W
S2 CS BT", bears S27½°E., 113.7'.
See sketch in file
Note - East - West fence line is 10' North of corner.

Douglas Co. Surveyors Office - John Pike - Stephen J. Flause
- 4/14/2008 - C.S. File 67/25-41

Fd. BC & 3 live BTs

Fd. OK by Kris DeGroot, 6/2009 - 2009-0034A&B
