

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 35

Alias	Description

BLM subd. of section by Peterson & Bedell under Group #1425 -Survey, April 1988-April 1990 (DCSO records, Vol. 49 Pg. 18725)

-----  
Point for the center ¼ sec. cor. of sec. 35, at intersection with the E. and W. center line.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd: T 28 S R 5 W  
C¼ S 35  
1988

from which

A Fir 11" dia., bears N.71°E., 29 lks. dist. mkd.  
C ¼ S35 BT.

A Fir 5" dia., bears S.36°W., 33 lks. dist., mkd.  
X BT.

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -  
Stephen J. Flause - 2/6/2009 - C.S. File 67/28-17

-----  
Found - BLM BC/IP (properly mkd) protrudes 4" out of ground.  
5" now 10" dia., D.Fir with fully healed blaze bears  
S.36°W., 21.5 ft. (1988)

11" now 12" dia., dead D.Fir with a partially healed  
blaze N.71°E., 18.6 (Rec. N.71°E., 19.1 ft.) 1988

New - 28" dia. D.Fir single blazed & scribed "C¼ S35 CS  
BT", bears S.47°E., 13.5 ft.

16" dia, D.Fir double blazed & scribed C¼ S35 CS  
BT", bears N.63°W., 4.6 ft.

Note - Compass decl. 16½°E.