

TOWNSHIP 28 RANGE 05 POINT IDENTIFIER # 540200

PRIMARY CORNER DESCRIPTION 1/4 Cor. secs. 26 & 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - A.R. Flint & L.L. Williams under Contract #151 dated May 23, 1871 (DCSO records, Vol. 13 Page 5688)

Set post at $\frac{1}{4}$ sec. corner, from which
A Laurel 4" dia., bears N.85°E., 6 lks. dist.
A Fir 4" dia., bears S.37°W., 5 lks. dist.

Bureau of Land Management resurvey by Peterson & Bedell under Group #1425 - Survey, April 1988-April 1990 (DCSO records, Vol. 49 Page 18704)

Point for the $\frac{1}{4}$ sec. cor. at proportionate distance; there is no remaining evidence of the original corner.
Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd: T 28 S R 5 W

$\frac{1}{4}$ S 26
S 35
1988

from which

A Fir 4" dia., bears S. $3\frac{1}{2}$ °W., 35 lks. dist. mkd X BT.
A Fir 6" dia., bears N. $73\frac{3}{4}$ °W., 31 lks. dist., mkd.
 $\frac{1}{4}$ S26 BT.

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.