

TOWNSHIP 28 RANGE 05 POINT IDENTIFIER # 540300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 23 and 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - A.R. Flint; L.L. Williams, under Contract #151 dated May 23, 1871 (DCSO records, Vol. 13 Page 5690)

-----  
Set post to  $\frac{1}{4}$  sec. corner, from which  
A W.Oak 4" dia., bears N.85°W., 35 lks. dist.  
A W.Oak 3" dia., bears S.35°E., 30 lks. dist.

BLM resurvey by Bedell and Peterson, under Group #1425 - Survey, April 1988-April 1990 (DCSO records, Volume 49 Page 18706)

-----  
Point for the  $\frac{1}{4}$  sec. corner, at proportionate distance; there is no remaining evidence of the original corner.  
Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd: T 28 S R 5 W

$\frac{1}{4}$   $\frac{S\ 23}{S\ 26}$   
1988

from which  
An Oak 12" dia., bears S.24 $\frac{1}{2}$ °W., 96 lks. dist., mkd.  
 $\frac{1}{4}$  S26 BT.  
A Cedar 10" dia., bears N.20  $\frac{3}{4}$ °W., 49 lks. dist.,  
mkd.  $\frac{1}{4}$  S23 BT.  
Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.