

PRIMARY CORNER DESCRIPTION Sec. Cor 35 & 36; 1 & 2 of T29-5

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - Elder and Gile, under Contract #31 dated April 7, 1853 (DCSO records, Vol. 13 Page 5650)

Set post corner to secs. 35, 36, 1 and 2, from which
A Y.Oak 12" dia., bears S.9°W., 21 lks. dist.
A Y.Oak 14" dia., bears N.6°W., 30 lks. dist.
A Y.Oak 12" dia., bears S.64°E., 34 lks. dist.
A Y.Oak 9" dia., bears N.62°E., 30 lks. dist.

H.L. Eppstein, DCS - Witness: Wolford, Ashcraft - Feb. 21, 1921 - Field Book 54 Page 42

I renewed this corner from two OBTs which were alive and standing with scribe marks chopped out and visible. Other trees gone. Set rock 6" x 6" x 14" for corner. Marked new trees as follows:

- Fir 10" dia., bears N.45°E., 40 lks.
- Fir 10" dia., bears S.65°E., 26 lks.
- Fir 8" dia., bears S.35°W., 16 lks.
- Fir 10" dia., bears N.29°W., 21 lks.

Doug. County Surveyors Office - James Byron, Deputy - April-May 1957 - C.S. File 47/180

Found - All of Cole's BTs. The NE BT is a stump only and rotted face well scribed. All other BTs down and rotted but some scribing visible. All BTs check for bearing and distance.

Set an Iron pipe with brass cap at cor. mkd: 35 36 T28S
2 1 T29S R5W
Surveyors Office, 1957

Blaze and scribe:

- 4" Laurel S.8½°W., 57.4 ft. mkd. S2 CS BT.
- 54" R.Fir S.24°E., 72.2 ft. mkd. S1 T29S R5W CS BT.
- 4" R.Fir N.18½°W., 22.0 ft. mkd. S35 CS BT.
- 4" Laurel N.46°E., 25.1 ft. mkd. S36 CS BT.

Fd OK, Wm. Ruppert, Jan/Mar. 1983, M 93-68

BLM resurvey by Peterson & Bedell under Group #1425. Survey dated April, 1988-April 1990 (DCSO records, Vol. 49 Pages 18689-90)

Sec. cor. on S. bdy. of tsp, perpetuated and recorded by J.W. Cole, in 1921, from original evidence no longer in existence, and further perpetuated and recorded by James Byron, in 1957, monumented with an I.P. 1¼" dia., firmly set., projecting 10" above ground (Cont. Next Page)

TOWNSHIP 28 RANGE 05 POINT IDENTIFIER # 600100

PRIMARY CORNER DESCRIPTION Sec. Cor. 35 & 36; 1 & 2, T29-5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which the remains of the bearing trees by Byron
A Madrone 8" dia., bears N.46 3/4°E., 37 lks. dist.
with healed blaze.
A sawed Fir stump 55" dia., bears S.25°E., 109 lks.
dist., no visible marks.
A Madrone 10" dia., bears S.8°W., 87 lks. dist., with
healed double blaze.
A Fir stump 13" dia., bears N.19½°W., 33½ lks. dist.
with healed double blaze.
and new bearing trees
A Fir 13" dia., bears S.17°E., 42 lks. dist.
mkd. T29S R5W S1 BT.
A Fir 20" dia., bears N.9½°W., 58 lks. dist.
mkd. T28S R5W S35 BT.
The corner is located on the SE side of the corner post of
barbed wire fences extending N. and W., and a woven wire
fence extending E.

FD OK by Raymond Brown, LS 2391 - For: Umpqua Youth, Inc. -
Jan. 1994 - 1994-0021 A & B

Fd. 4 BTs & BC. Ok by H.Christensen - 11/97 - M 128-14