

TOWNSHIP 28 RANGE 05 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Sec. Cor. 25, 26, 35 & 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - A.R. Flint and L.L. Williams, under Contract #151 dated May 23, 1871 (DCSO records, Vol. 13 Page 5683)

Set post to corner secs. 25, 26, 35 and 36, from which
An Ash 18" dia., bears N.45°E., 105 lks. dist.
A B.Oak 12" dia., bears N.5°E., 140 lks. dist.
A Laurel 24" dia., bears S.50°W., 140 lks. dist.
A Laurel 24" dia., bears S.20°E., 125 lks. dist.

J.H. Markham, Jr. Engineer - Sept 21, 1949 - C.S. File 40/206

Corner determined from the remains of an old BT, dead Ash laying on the ground bears N.45°E., 70.0 ft. Old scribing is very plain.
Set an Iron post 30" ong 3/4" dia., 24" in ground, from which
10" Fir bears S.38°E., 33 ft. mkd. S 36 2880 BT.
18" B.Oak bears S.23°W., 50 ft. mkd. S 35 2880 BT.
15" Cedar bears N.37°W., 3.0 ft. mkd. S 26 2880 BT.
11" Fir bears N.73°E., 18 ft. mkd. S 25 2880 BT.

Doug. County Surveyors Office - James Byron, Deputy - Dale McFarland; John Powell - Dec. 1961 - C.S. File 49/64-44

Found - 1" I.P. at corner and all Markham's BTs.
Orig. SW & NE BTs, show scribing.
B.Oak now 20", S.23°W., 55.8 ft., shows scribing on partly closed face.
Rescribe orig. 24" now 40" Laurel, S.20°E., 80.0 ft. "S36 T28S R5W CS BT".
New BTs -16" Cedar bears N.68°W., 10.8 ft. scribed S26 T28S R5W CS BT.
12" R.Fir bears N.36½°E., 49.3 ft. scribed S25 T28S R5W CS BT.
1" I.P. at corner is OK. Markham NW BT is down. NE & SE BTs now snags.
DID NOT SET BRASS CAP.

Bruce Shaner, For: C & D Lumber - August 1964 - M 22-58

Found - 1" I.P. from which:
16" Cedar stump w/scribes visible bears N.68°W., 10.8 ft.
12" D.Fir w/scribes visible bears N.36½°E., 49.3 ft.
40" Madrone stump bears S.20°E., 78.4 ft.
20" Oak now blown down, with face & BT tag, bears S.24°W., 53.7 ft.
New BTs -20" Oak, scribed "T28S R5W S36 BT" bears S.57°E., 80.9 ft. (Cont. Next Page)

TOWNSHIP 28 RANGE 05 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Sec. Cor. 25, 26, 35, 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

42" Madrone, scribed "T28S R5W S35 BT" bears S.63°W., 87.7 ft.
 6" Madrone, scribed "T28S R5W S26 BT" bears N.84°W., 46.3 ft.

Found OK, Burton Holt, April 1981, M 87-56

BLM resurvey by Peterson and Bedell under Group #1425 - Survey April 1988-April 1990 (DCSO records, Vol. 49 Pages 18696-97)

Cor. perpetuated & recorded by Markham in 1949, further perpetuated & recorded by Byron in 1961, & further perpetuated & recorded by Shaner in 1964, monumented with an I.P. 1" dia., firmly set, projecting 10" above ground, from which the remains of the original bearing trees:

- A root hole, bears N.45°E., 105 lks. dist., with a down ash alongside, 25" dia., with scribe mark R visible on an open rotted blaze.
- A Madrone snag 40" dia., bears S.22½°E., 121 lks. dist. with scribe marks BT visible on a partially healed blaze. (Record S.20°E., 125 lks.)
- A Madrone 46" dia., bears S.64°W., 126 lks. dist., with illegible scribe marks visible on the opened original blaze & illegible scribe marks visible on a partially healed blaze made by Shaner. (Rec. S.50°W., 140 lks.)

and a bearing tree mkd. by Byron

- A Fir 20" dia., bears N.35¼°E., 76 lks. dist., with healed blaze.

and a bearing tree mkd. by Shaner

- An Oak 25" dia., bears S.56°E., 126 lks. dist. with healed blaze.

At the corner point
 Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd: T 28 S R 5 W

S 26	S 25
S 35	S 36

1988

from which new bearing trees

- A Fir 8" dia., bears S.12½°W., 63 lks. dist., mkd. T28S R5W S35 BT.
- A Cedar 8" dia., bears N.26¼°W., 67 lks. dist., mkd. T28S R5W S36 BT.

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

Fd. BC 4/2022 - Bart Heichel - M180-80 _____