

TOWNSHIP 28 RANGE 05 POINT IDENTIFIER # 600240

PRIMARY CORNER DESCRIPTION 1/4 Cor. secs. 25 and 26

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

Original - A.R. Flint & L.L. Williams, under Contract #151 dated May 23, 1871 (DCSO records, Vol. 13 Page 5684)

Set post to 1/4 sec. corner, from which
A Fir 4" dia., bears S.32°W., 68 lks. dist.
A Cedar 6" dia., bears S.35°E., 90 lks. dist.

Bruce Shaner, For: C & D Lumber Co. - Aug. 1964 - M 22-58

Set - 5/8" Iron rod, from which a:
12" Cedar, orig. BT, with scribes visible, now blown down, bears S.35°E., 59.4 ft.
26" D.Fir, orig. BT, I rescribed "1/4 S S26 BT" bears S.35°W., 44.0 ft. (Rec. S.32°W., 44.9 ft.)
16" Cedar, I scribed "1/4 S S25 BT" bears N.35°E., 74.1 ft.

BLM resurvey by Peterson & Bedell, under Group #1425 - Survey, April 1988-April 1990 - (DCSO records Vol. 49 page 18699)

The 1/4 corner, perpetuated & recorded by Bruce Shaner, in 1964, determined from the remains of the original bearing trees:

A root hole, bears S.34 1/4°E., 90 lks. dist., with a down cedar alongside, 16" dia., with an opened burned blaze. (Record, S.35°E.)
A Fir 28" dia., bears S.36°W., 68 lks. dist., with healed blaze. (Record, S.32°W.)
and a bearing tree mkd. by Shaner
A Cedar 18" dia., bears N.34 1/2°E., 115 lks. dist., with a partially healed burned blaze.

At the corner point
Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd: T 28 S R 5 W

1/4
S 26 S 25
1988

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.