

PRIMARY CORNER DESCRIPTION Sec. Cor. 23, 24, 25 & 26

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - A.R. Flint; L.L. Williams, under Contract #151 dated May 23, 1871 (DCSO records, Vol. 49 Pages 5684-85)

Set post to corner of secs. 23, 24, 25 & 26, from which
A Boulder 4 ft. above ground, mkd X, bears N.46°E., 250 lks.
A Boulder 5 ft. over, marked X, bears S.45°W., 410 lks. dist.

Placed around the stake a pile of stones. No trees in reasonable distance.

This corner is on the summit of ridge about ¼ of a mile from highest point of Dodson Mountains.

Bruce A. Shaner, for: C & D Lumber Co. - Aug. 1964 - M 22-58

Set - 5/8" x 36" Iron rod from which a:
Rock, 6 ft. high & 20 ft. x 30 ft. wide bears East 198.0 ft. to E. face of said big rock.
"Dodson" Bench Mark set by USC & GS in 1942 on above big rock bears N.88°E., 190.7 ft.
A Boulder, 5.0 ft. high, I scribed "X", bears S.45°W., 353.0 ft. (Rec. S.45°W., 270.6 ft.)
A Boulder, originally 4.0 ft. high, now 2.0 ft. high, bears N.46°E., 214.0 ft. (Rec. N.46°E., 165.0 ft.)

Found OK, L. Dolan, May, 1986, M 100-79

BLM resurvey by Peterson & Bedell under Group #1425, Survey, April 1988-April 1990 (DCSO recs. Vol. 49 Page 18700)

Found corner, perpetuated & recorded by Bruce Shaner in 1964, monumented with an iron rod, 5/8" dia., firmly set, projecting 4" above ground, from which an original topographic feature:

The center of the easterly edge of a rock outcrop, 50 x 35 x 9 ft. high, long side bears E. and W., bears N.89°34'E., 3.00 chs. dist.

and the original bearing objects:

The top center of a rock outcrop, 6 x 5 x 1¼ ft. high, bears N.43°E., 327 lks. dist., no visible marks. (Rec. 4 ft. above ground, N.46°E., 250 lks.)

The top center of a rock outcrop, 20 x 12 x 8 ft. high, bears S.46°W., 547 lks. dist., no visible marks. (Rec. 5 ft. above ground, S.45°W., 410 lks.)

At the corner point

(Cont. Next Page)

TOWNSHIP 28 RANGE 05 POINT IDENTIFIER # 600300

PRIMARY CORNER DESCRIPTION Sec. cor. for 23, 24, 25 & 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd: T 28 S R 5 W

S 23 | S 24
S 26 | S 25
1988

from which a new reference monument

A brass tablet, 3¼" dia., with a 3½" stem cemented into a drill hole, in the SW. cor. of a rock outcrop, 6 x 4 x 4 ft. high, for a reference monument, bears N.55°19'E., 3.038 chs. dist., mkd. RM T28S R5W S24 200.5 ft. 1988 and an arrow pointing to the corner.

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

The corner is located in a wire fence line, extending E. and W.

From this point, United States Coast and Geodetic Survey triangulation station "DODSON" bears N.14°02'00" E., 34.619 chs. dist., monumented with a bronze disk, cemented into solid rock, mkd. DODSON 1942.

From this same point, a United States Coast and Geodetic Survey azimuth mark, bears N.85°44'E., 2.887 chs. dist., monumented with a bronze disk, 4" dia., cemented into solid rock, mkd. DODSON 1942 and an arrow pointing northerly.

Found Brass cap, August, 1990, M 110-57

Found OK, by Whitson, Feb. 1992, Partition 1992-0014

Fd. Ok by Kris DeGroot, 8/2009 - M159-69